Rev. 07-24-15		HWAY BRIDG N OF ACTION		ר	TDOT Department of Transportation
BRIDGE ROA CR	NUMBER: 66015260001 OWNER: OBION COUNTY ND NAME: HANK MILLER D ROSSING: RICHLAND CREEK NTITUDE:: N 36.29811 DEGREE	s		COUNTY: ROUTE: SPECIAL CASE: COUNTY SEQUENCE: LOG MILE:	01526 0 1
LON	NGITUDE: W 89.24703 DEGREE	S		YEAR BUILT:	1970
		- TYPE OF SUPER	STRUCTURE -		
MAIN SPAN:	PRESTRESSED CONCRETE - BOX GIRDERS - MULTIPLE	BEAM OR	APPR. SPAN:	NOT APPLICABLE	
		- TYPE OF SUBS			
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTM	ENT ON UNKNOWN	FOUNDATION		
BENTS:	NOT APPLICABLE				
PIERS:	NOT APPLICABLE				
		SCOUR EVAL			
	unknown foundations. Risk of so icant flood events. Monitor bridg				for distress
		- INSPECTION PR	OCEDURES -		
What Initiat	ed the Call-out Inspection?	[] BridgeW	atch Alert		
		[] TDOT Di	strict or Loca	al Maintenance Personn	el
		[] THP or L	ocal Law Enf	orcement Personnel	

Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
 - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.

[] Other:

- 2. Check for plumb of piers or bents.
- [] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [] Review the latest bridge inspection report versus current field conditions

If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
 - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
 - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
 - (4) TDOT Regional Bridge Engineer
- [] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

P	UΒ	LIC	ATIC)N	DAT	Έ

07-Nov-24



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(731) 885-9611
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 885-5960
COUNTY SHERIFF'S OFFICE	(731) 885-5832

[] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

COMMENTS: _____

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

Range Pole

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)

PUBLICATION DATE