HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 66015340007

BRIDGE OWNER: OBION COUNTY

ROAD NAME: MT ZION RD

CROSSING: N. REELFOOT CREEK COUI

LATITUDE:: N 36.47939 DEGREES
LONGITUDE: W 89.07453 DEGREES

ROUTE: 01534
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 8.14

COUNTY: OBION

LON	IGITUDE: W 89.07453 DEGR	EES		YEAR BUILT: 1975	
		TYPE OF S	SUPERSTRUCTURE =		
MAIN SPAN:	PRESTRESSED CONCRETE - BO	OX BEAM OR	APPR. SPAN:	NOT APPLICABLE	
		TYPE OF	SUBSTRUCTURE -		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUT	MENT ON UNK	NOWN FOUNDATION		
BENTS:	NOT APPLICABLE				
PIERS:	NOT APPLICABLE				
		scou	R EVALUATION =		
Bridge is sco	our critical, but countermeasu	res have beer	installed to reduce	the risk of bridge failure during a flood	
event. Deter				OOT for assessment. Rip-rap protection has	
		- INSPECTI	ON PROCEDURES -		
What Initiated the Call-out Inspection?		[] Bri	dgeWatch Alert		
		[] TD	OT District or Loca	al Maintenance Personnel	
		[] TH	P or Local Law En	forcement Personnel	
		[] Ot	her:		
Things to c	heck on a bridge during flo	ods:			
	movement - horizontally as		-		
		_	ırb line, both bridg	e rails and outer edge of bridge deck.	
	Check for plumb of piers or	bents.			
	k for embankment erosion				
	k for drift build-up on piers				
	k pier exposure, if possible	-	•		
[] - Revie	ew the latest bridge inspect	on report ve	rsus current field c	onditions	
lf Closure is	recommended:				
Coun temp	ity or City Maintenance Per	sonnel. Use E torists to sta	Barricade Tape, traf	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may	
[] - Conta	act: (1) District Maintenanc	e Supervisor	(if bridge is State	maintained)	
	(2) City or County Highway Maintenance Official (if bridge is not State maintained)				
	(3) Tennessee Highway	/ Patrol and/o	or local law enforce	ement Officers as appropriate	
	(4) TDOT Regional Brid	lge Engineer			
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.				

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



officials in establishing a detour route. Any brid prior to signing the detour route.	ge on the selected detour route shall be checked			
[] - The bridge can be re-opened only after a TDOT	ridge can be re-opened only after a TDOT bridge inspection team checks the substructure and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:			
COUNTY MAYOR'S OFFICE	(731) 885-9611			
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 885-5960			
COUNTY SHERIFF'S OFFICE	(731) 885-5832			
as appropriate, photographs of the bridge and so scouring has occurred, the report shall also be comments:	copied to Bridge Inspection Headquarters.			
Suggested List of Equipment to conduct the Inspection	<u>n:</u>			
Latest Bridge Inspection Report Scour POA Report with the above Checklist				
Bridge Design Plans, if available				
Tape measure with weight				
Plumb bob				
Range Pole				
A 1000 Foot Roll of yellow Polyethylene Barricade Tap SAFETY HAZARD KEEP A				
A Barricade Tape Dispenser with serrated cutter				
A roll of Duct Tape				
Traffic Cones - Minimum of four (4)				
Traffic Safety Flares - Minimum of four (4) or set of ele	ectronic warning flashers			

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)