HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 660A1390001
BRIDGE OWNER: OBION COUNTY

ROAD NAME: ANDREW WHEELER LANE
CROSSING: N FORK HOOSIER CREEK
LATITUDE:: N 36.44908 DEGREES
LONGITUDE: W 89.10506 DEGREES

COUNTY: OBION
ROUTE: 0A139
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.81

LON	NGITUDE: W 89.10506 DEGREES	}	YEAR BUILT: 1975
MAIN SPAN:	CONCRETE - CHANNEL BEAM	TYPE OF SUPERSTRUCTURE = APPR. SPAN:	NOT APPLICABLE
		TVDE OF CURCURETURE	
ADLITMENTS.	CONCRETE CTUR ARUTMENT ON I	TYPE OF SUBSTRUCTURE =	
	CONCRETE STUB ABUTMENT ON U	JAKNOWN FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
	unknown foundations. Risk of sco icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
			al Maintenance Personnel
		[] THP or Local Law En	forcement Personnel
		-	
Things to c	heck on a bridge during floods	<u>s:</u>	
1. (movement - horizontally as w Check displacement / deflectio Check for plumb of piers or be	n along curb line, both bridge	e rails and outer edge of bridge deck.
[] - Chec	k for embankment erosion		
[] - Chec	k for drift build-up on piers or	bents	
[] - Chec	k pier exposure, if possible, ar	nd compare to previous inspe	ection
[] - Revie	ew the latest bridge inspection	report versus current field c	onditions
lf Closure is	recommended:		
[] - Stay Cour temp	at bridge with vehicle pulled a nty or City Maintenance Persor	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State	maintained)
	• •	•	idge is not State maintained)
	() ,	•	ement Officers as appropriate
	(4) TDOT Regional Bridge		
[] - The E	()	•	daylight visual inspection is made
	TDOT bridge inspection team.		, <u>0</u>

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route. 	e District maintenance or local highway maintenance dge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 885-9611		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 885-5960		
COUNTY SHERIFF'S OFFICE	(731) 885-5832		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection	<u>on:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap			
SAFETY HAZARD KEEP A	AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24