HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 660A5900001 COUNTY: OBION
BRIDGE OWNER: TOWN OF TROY
ROAD NAME: WOLVERINE RD
CROSSING: BRANCH
LATITUDE:: N 36.32839 DEGREES
COUNTY SEQUENCE: 1
LOG MILE: 0.39

LATITUDE:: N 36.32839 LOG MILE: 0.39 LONGITUDE: W 89.15825 **DEGREES** YEAR BUILT: 2004 TYPE OF SUPERSTRUCTURE MAIN SPAN-**CONCRETE - CHANNEL BEAM** APPR. SPAN: NOT APPLICABLE TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE STUB ABUTMENT ON UNKNOWN FOUNDATION BENTS: **NOT APPLICABLE** PIERS: **NOT APPLICABLE** SCOUR EVALUATION Bridge has unknown foundations. Risk of scour cannot be determined. The bridge shall be monitored for distress during significant flood events. Monitor bridge in lieu of installing scour countermeasures. **INSPECTION PROCEDURES** [] BridgeWatch Alert What Initiated the Call-out Inspection? [1 TDOT District or Local Maintenance Personnel [] THP or Local Law Enforcement Personnel [] Other: Things to check on a bridge during floods: [] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [] - Check for embankment erosion [] - Check for drift build-up on piers or bents [] - Check pier exposure, if possible, and compare to previous inspection [] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained) (2) City or County Highway Maintenance Official (if bridge is not State maintained)

PUBLICATION DATE

07-Nov-24

BRIDGE ID 660A5900001

(3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate

[] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

(4) TDOT Regional Bridge Engineer

by a TDOT bridge inspection team.

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	g a detour route. Any bridge	strict maintenance or local highway maintenance on the selected detour route shall be checked
	pened only after a TDOT brid rmined to be structurally sta	dge inspection team checks the substructure able.
CONTACT PERSONNEL:		TELEPHONE NUMBER:
CITY MAYOR'S OFFICE		(731) 536-4745
POLICE OFFICE		(731) 536-4745
PUBLIC WORKS DIRECTOR		(731) 536-4745
The report shall include as appropriate, photogr	the date and time of the instaphs of the bridge and stre	n to BridgeWatch scour monitoring system. spection, a brief summary of findings and, am channel measurements. If significant pied to Bridge Inspection Headquarters.
COMMENTS:		
Suggested List of Equipment	to conduct the Inspection:	
Latest Bridge Inspection Rep		
Scour POA Report with the al		
Bridge Design Plans, if availa	ble	
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Po	lyethylene Barricade Tape p	printed with the following message:
5	SAFETY HAZARD KEEP AWA	AY

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24