HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 660A5900003 BRIDGE OWNER: OBION COUNTY ROAD NAME: W WOLVERINE RD CROSSING: MILL CREEK

LATITUDE:: N 36.28478 DEGREES

COUNTY: OBION ROUTE: 0A590 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 3.64

| LON | GITUDE: W 89.16903 DEGREE | 3 | YEAR BUILT: 1992 |
|---|---|---|--|
| | | TYPE OF SUPERSTRUCTURE | |
| MAIN SPAN: | PRESTRESSED CONCRETE - STRI OR GIRDER | | NOT APPLICABLE |
| | | TYPE OF SUBSTRUCTURE | |
| ABUTMENTS: | CONCRETE STUB ABUTMENT ON | CONCRETE PILE FOUNDATION | |
| BENTS: | CONCRETE PILE BENT ON PILE FO | DUNDATION | |
| PIERS: | NOT APPLICABLE | | |
| | | SCOUR EVALUATION | |
| | | our cannot be determined. The | bridge shall be monitored for distress |
| auring signiti | cant flood events. Monitor bridg | e in lieu of installing scour coul | ntermeasures. |
| | | INSPECTION PROCEDURES | |
| What Initiated the Call-out Inspection | | [] BridgeWatch Alert | |
| | | [] TDOT District or Loc | al Maintenance Personnel |
| | | [] THP or Local Law En | forcement Personnel |
| | | [] Other: | |
| | | | |
| Things to ch | <u>neck on a bridge during flood</u> | <u>s:</u> | |
| 1. C 2. C [] - Check [] - Check [] - Check | movement - horizontally as we heck displacement / deflection heck for plumb of piers or be for embankment erosion of for drift build-up on piers or pier exposure, if possible, a we the latest bridge inspection | n along curb line, both bridg nts. bents nd compare to previous insp | |
| f Closure is | recommended: | | |
| Countempo | ty or City Maintenance Perso | nnel. Use Barricade Tape, tra rists to stay off of the bridge | cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may |
| [] - Conta | ct: (1) District Maintenance S | Supervisor (if bridge is State | e maintained) |
| | (2) City or County Highwa | y Maintenance Official (if b | ridge is not State maintained) |
| | (3) Tennessee Highway P | atrol and/or local law enforce | ement Officers as appropriate |
| | (4) TDOT Regional Bridge | Engineer | - - |
| | ridge should remain closed ι ΓDOT bridge inspection team. | | daylight visual inspection is made |

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



| offic | | te District maintenance or local highway maintenance idge on the selected detour route shall be checked | |
|------------------|---|---|--|
| | he bridge can be re-opened only after a TDOT bridge inspection team checks the substructure nits and they are determined to be structurally stable. | | |
| CONT | ACT PERSONNEL: | TELEPHONE NUMBER: | |
| COUN | NTY MAYOR'S OFFICE | (731) 885-9611 | |
| HWY. | CHIEF ADMINISTRATOR'S OFFICE | (731) 885-5960 | |
| COUN | ITY SHERIFF'S OFFICE | (731) 885-5832 | |
| The r | eport shall include the date and time of the propriate, photographs of the bridge and | ection to BridgeWatch scour monitoring system. see inspection, a brief summary of findings and, stream channel measurements. If significant copied to Bridge Inspection Headquarters. | |
| COMMENTS | | | |
| <u>Suggested</u> | List of Equipment to conduct the Inspect | ion: | |
| | ge Inspection Report | | |
| | Report with the above Checklist | | |
| _ | ign Plans, if available | | |
| - | ure with weight | | |
| Plumb bob | | | |
| Range Pole | | one printed with the following message: | |
| A IUUU FOO | ot Roll of yellow Polyethylene Barricade Ta SAFETY HAZARD KEEP | | |
| | SAFELL HAZARD NEEP | AVAI | |

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape