## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 66F00250001

BRIDGE OWNER: OBION COUNTY

ROAD NAME: OLD TURNPIKE RD

CROSSING: BRANCH

CRUSSING. BRANCH

LATITUDE:: N 36.30289 DEGREES LONGITUDE: W 89.13058 DEGREES

COUNTY: OBION
ROUTE: 01524
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 5.67

LON	NGITUDE: W 89.13058 DEGREES	YEAR BUILT: 1950
MAIN SPAN:	CONCRETE - TEE BEAM	TYPE OF SUPERSTRUCTURE  APPR. SPAN: NOT APPLICABLE
WAIN SPAN.	CONCRETE - TEE BEAM	
		TYPE OF SUBSTRUCTURE
	CONCRETE FULL HEIGHT ABUTME	NT ON UNKNOWN FOUNDATION
BENTS:	NOT APPLICABLE	
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
		our cannot be determined. The bridge shall be monitored for distress ntermeasures are installed but they are needed.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert
	·	[ ] TDOT District or Local Maintenance Personnel
		THP or Local Law Enforcement Personnel
		[ ] Other:
Things to c	heck on a bridge during floods	<u>s:</u>
[ ] - Span	movement - horizontally as w	ell as vertically
		n along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	
	k for embankment erosion	
	k for drift build-up on piers or	hents
	• •	nd compare to previous inspection
		report versus current field conditions
[ ] - Kevie	w the latest bridge mapection	report versus current neid conditions
If Closure is	recommended:	
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, anel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
-	• •	Supervisor ( if bridge is State maintained )
	` '	y Maintenance Official ( if bridge is not State maintained )
	,,,,	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	
[ ] - The F	( )	ntil the water recedes and a daylight visual inspection is made
	TDOT bridge inspection team.	, <del>, , , , , , , , , , , , , , , , , , </del>

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ork with State District maintenance or local highway maintenance oute. Any bridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 885-9611		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 885-5960		
COUNTY SHERIFF'S OFFICE	(731) 885-5832		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduc	t the Inspection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Check	klist		
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
	Barricade Tape printed with the following message:		
SAFETY HA	ZARD KEEP AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24