

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: **66SR0030030**
 BRIDGE OWNER: **STATE OF TENNESSEE**
 ROAD NAME: **S US HWY 51**
 CROSSING: **OBION RIVER**
 LATITUDE: **N 36.23989 DEGREES**
 LONGITUDE: **W 89.21731 DEGREES**

COUNTY: **OBION**
 ROUTE: **SR003**
 SPECIAL CASE: **0**
 COUNTY SEQUENCE: **1**
 LOG MILE: **2.38**
 YEAR BUILT: **1978**

TYPE OF SUPERSTRUCTURE

MAIN SPAN: **PRESTRESSED CONCRETE CONTINUOUS - STRINGER/MULTI-BEAM OR GIRDER** APPR. SPAN: **NOT APPLICABLE**

TYPE OF SUBSTRUCTURE

ABUTMENTS: **CONCRETE STUB ABUTMENT ON CONCRETE PILE FOUNDATION**
 BENTS: **NOT APPLICABLE**
 PIERS: **CONCRETE COLUMNS WITH SOLID WEB WALL (DUMB BELL) ON CONCRETE PILE FOUNDATION**

SCOUR EVALUATION

Bridge is scour critical; bridge foundations determined to be unstable for calculated scour conditions. Rip-rap protection has been installed and is in good condition.

INSPECTION PROCEDURES

What Initiated the Call-out Inspection? BridgeWatch Alert
 TDOT District or Local Maintenance Personnel
 THP or Local Law Enforcement Personnel
 Other: _____

Things to check on a bridge during floods:

- Span movement - horizontally as well as vertically
 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.
 2. Check for plumb of piers or bents.
- Check for embankment erosion
- Check for drift build-up on piers or bents
- Check pier exposure, if possible, and compare to previous inspection
- Review the latest bridge inspection report versus current field conditions

If Closure is recommended:

- Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
 (2) City or County Highway Maintenance Official (if bridge is not State maintained)
 (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
 (4) TDOT Regional Bridge Engineer
- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

PUBLICATION DATE

17-Apr-19

BRIDGE ID
66SR0030030

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



- [] - The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:

TELEPHONE NUMBER:

REGION BRIDGE ENGINEER

(731) 234-9561

DISTRICT MAINTENANCE SUPERVISOR

(731) 571-8883

TENNESSEE HIGHWAY PATROL

(901) 543-6256

- [] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

COMMENTS: _____

Suggested List of Equipment to conduct the Inspection:

- Latest Bridge Inspection Report
- Scour POA Report with the above Checklist
- Bridge Design Plans, if available
- Tape measure with weight
- Plumb bob
- Range Pole
- A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:
SAFETY HAZARD KEEP AWAY
- A Barricade Tape Dispenser with serrated cutter
- A roll of Duct Tape
- Traffic Cones - Minimum of four (4)
- Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers
- TDOT two-way radio (State Personnel only) and/or cellular telephone
- TDOT radio directory (State Personnel only)

PUBLICATION DATE

17-Apr-19

BRIDGE ID
66SR0030030