## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 680A3070001

BRIDGE OWNER: PERRY COUNTY

ROAD NAME: PINE SPRINGS RD.

CROSSING: S FK TOM'S CREEK

LATITUDE:: N 35.71325 DEGREES

ROUTE: 0A307 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 0.12 YEAR BUILT: 1993

COUNTY: PERRY

LONGITUDE: W 87.86408 DEGREES		YEAR BUILT: 1993	
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	R GIRDER APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON CONCRETE SPREAD FOOTING FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
•		our cannot be determined. The bridge shall be monitored for distress e in lieu of installing scour countermeasures.	
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
	·	The strict of Local Maintenance Personnel	
		THP or Local Law Enforcement Personnel	
		[ ] Other:	
Things to c	heck on a bridge during floods	<u>s:</u>	
[ ] - Span	movement - horizontally as w	ell as vertically	
		n along curb line, both bridge rails and outer edge of bridge deck.	
	Check for plumb of piers or be		
[ ] - Chec	k for embankment erosion		
[ ] - Chec	k for drift build-up on piers or	bents	
		nd compare to previous inspection	
[ ] - Review the latest bridge inspection report versus current field conditions			
	3 .	•	
<u>If Closure is</u>	recommended:		
Coun temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may	
[ ] - Contact: (1) District Maintenance Supervisor ( if bridge is State maintained )			
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )	
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer	
	<ul> <li>The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.</li> </ul>		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



<ul> <li>The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route.</li> </ul>	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
[ ] - The bridge can be re-opened only after a TDOT units and they are determined to be structurally	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 589-2216		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 589-5217		
COUNTY SHERIFF'S OFFICE	(931) 589-8803		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection Latest Bridge Inspection Report	<u>vn:</u>		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap			

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape