HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 710A0120001
BRIDGE OWNER: PUTNAM COUNTY
ROAD NAME: MADDUX CEMETERY RD.
CROSSING: BIG INDIAN CREEK

LATITUDE:: N 36.13935 DEGREES LONGITUDE: W 85.77628 DEGREES

COUNTY: PUTNAM
ROUTE: 0A012
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.02
YEAR BUILT: 1935

		TYPE	OF SUP	ERSTRUCTURE =		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR			APPR. SPAN:	CONCRETE - TEE BEAM	
				7		
		TYP	E OF SU	BSTRUCTURE =		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN	T ON	UNKNOV	VN FOUNDATION		
BENTS:	NOT APPLICABLE					
PIERS:	CONCRETE SOLID SHAFT PIER ON I	JNKNO	OWN FO	JNDATION		
		s	COUR E	VALUATION =		
	unknown foundations. Risk of sco iicant flood events. Monitor bridge				bridge shall be monitored for distress termeasures.	
		INSP	ECTION	PROCEDURES =		
What Initiat	ed the Call-out Inspection?	r 1	Brida	eWatch Alert		
What initiated the San Sat inspection.		1 1	_		al Maintenance Personnel	
		1 1			forcement Personnel	
		1 1				
			011101	•		
Things to c	heck on a bridge during floods	<u>.</u>				
[] - Snan	movement - horizontally as we	ll as y	vertical	lv		
	•			•	e rails and outer edge of bridge deck.	
	Check for plumb of piers or ben		9	,	o rano anta o acor o ago or arra go acom	
	k for embankment erosion					
	k for drift build-up on piers or k	ents				
	• •			o previous inspe	ection	
[] - Check pier exposure, if possible, and compare to previous inspection[] - Review the latest bridge inspection report versus current field conditions						
[]	on the latest bridge mepeenen.	opo.				
If Closure is	recommended:					
Cour temp	nty or City Maintenance Personi	nel. U	lse Bar	ricade Tape, trat	cured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may	
[] - Conta	act: (1) District Maintenance Sเ	ıperv	isor (i	f bridge is State	maintained)	
	(2) City or County Highway	Mair	ntenan	e Official (if br	idge is not State maintained)	
	(3) Tennessee Highway Pa	trol a	nd/or le	ocal law enforce	ement Officers as appropriate	
	(4) TDOT Regional Bridge	Engir	neer		· · · · · · · · · · · · · · · · · · ·	
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 					

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any prior to signing the detour route.	bridge on the selected detour route shall be checked
[] - The bridge can be re-opened only after a TI units and they are determined to be structu	DOT bridge inspection team checks the substructure urally stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(931) 526-2161
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 526-4864
COUNTY SHERIFF'S OFFICE	(931) 528-8484
as appropriate, photographs of the bridge a	of the inspection, a brief summary of findings and, and stream channel measurements. If significant be copied to Bridge Inspection Headquarters.
Suggested List of Equipment to conduct the Insp	ection:
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
A 1000 Foot Roll of yellow Polyethylene Barricade	
SAFETY HAZARD KE	EP AWAY

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24