HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: ROANE

ROUTE: 02374

LOG MILE: 8 92

SPECIAL CASE: 0

BRIDGE ID NUMBER: 730A0860001 BRIDGE OWNER: ROANE COUNTY ROAD NAME: POPULAR CREEK RD CROSSING: DAVIDSON CREEK

COUNTY SEQUENCE: 1 LATITUDE:: N 35.95950 DEGREES LONGITUDE: W 84.40167 DEGREES

YEAR BUILT: 1979 TYPE OF SUPERSTRUCTURE PRESTRESSED CONCRETE - BOX BEAM OR APPR. SPAN: NOT APPLICABLE MAIN SPAN-**GIRDERS - MULTIPLE** TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE SPILL THROUGH ABUTMENT ON UNKNOWN FOUNDATION BENTS: **NOT APPLICABLE** PIERS: **NOT APPLICABLE SCOUR EVALUATION** Bridge has unknown foundations. Risk of scour cannot be determined. The bridge shall be monitored for distress during significant flood events. Monitor bridge in lieu of installing scour countermeasures. INSPECTION PROCEDURES What Initiated the Call-out Inspection? [] BridgeWatch Alert [] TDOT District or Local Maintenance Personnel [1 THP or Local Law Enforcement Personnel [] Other: Things to check on a bridge during floods: [] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [] - Check for embankment erosion [] - Check for drift build-up on piers or bents [] - Check pier exposure, if possible, and compare to previous inspection [] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained) (2) City or County Highway Maintenance Official (if bridge is not State maintained) (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate (4) TDOT Regional Bridge Engineer [] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	with State District maintenance or local highway maintenance e. Any bridge on the selected detour route shall be checked
[] - The bridge can be re-opened only after units and they are determined to be st	er a TDOT bridge inspection team checks the substructure tructurally stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(865) 376-5578
HWY. CHIEF ADMINISTRATOR'S OFFICE	(865) 882-9782
COUNTY SHERIFF'S OFFICE	(865) 376-5582
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 	
COMMENTS:	
Suggested List of Equipment to conduct the	e Inspection:
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
	ricade Tape printed with the following message:
SAFETY HAZAR	RD KEEP AWAY

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24