## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 730A2640001
BRIDGE OWNER: ROANE COUNTY
ROAD NAME: CHANDLEY RD
CROSSING: BUCK CREEK

LATITUDE:: N 35.83778 DEGREES
LONGITUDE: W 84.44310 DEGREES

COUNTY: ROANE
ROUTE: 0A404
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.51
YEAR BUILT: 1934

		TYPE OF SUPERSTRUCTURE	<u> </u>	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR			
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN	IT ON CONCRETE SPREAD FO	OOTING FOUNDATION	
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
Bridge has u	inknown foundations. Risk of scor		The bridge shall be monitored for distress	
•	cant flood events. Monitor bridge		•	
		INSPECTION PROCEDURES		
What Initiat	ad the Call out Increation?			
What Initiated the Call-out Inspection?		[ ] BridgeWatch Aler	ocal Maintenance Personnel	
			Enforcement Personnel	
			Emorcement Personner	
		[ ] Other.		
Things to c	heck on a bridge during floods			
[ ] - Snan	movement - horizontally as we	ll as vertically		
<ul> <li>Span movement - horizontally as well as vertically</li> <li>Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.</li> </ul>				
	Check for plumb of piers or ben	<u> </u>	lago lano ana cator cago el bilago acom	
[ ] - Check for embankment erosion				
[ ] - Check for drift build-up on piers or bents				
[ ] - Check pier exposure, if possible, and compare to previous inspection				
[ ] - Review the latest bridge inspection report versus current field conditions				
[ ] - Neview the latest bridge inspection report versus current field conditions				
If Closure is	recommended:			
<ul> <li>Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.</li> </ul>				
[ ] - Conta	act: (1) District Maintenance Su	pervisor ( if bridge is S	tate maintained )	
	(2) City or County Highway	Maintenance Official (i	if bridge is not State maintained )	
	(3) Tennessee Highway Pa	trol and/or local law enfo	orcement Officers as appropriate	
	(4) TDOT Regional Bridge			
	] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	tate District maintenance or local highway maintenance bridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(865) 376-5578		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(865) 882-9782		
COUNTY SHERIFF'S OFFICE	(865) 376-5582		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.     </li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report Scour POA Report with the above Checklist	ection:		
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:		
CAFETY HAZADD MEE	ED AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24