HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 760A1210003
BRIDGE OWNER: SCOTT COUNTY
ROAD NAME: SMITH CREEK RD
CROSSING: SMITH CREEK

LATITUDE:: N 36.46175 DEGREES
LONGITUDE: W 84.38042 DEGREES

COUNTY: SCOTT
ROUTE: 0A121
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.90
YEAR BUILT: 1920

LON	NGITUDE: W 84.38042 DEGREES		YEAR BUILT: 1920
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	TYPE OF SUPERSTRUCTURE = R GIRDER APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	MASONRY OR CONCRETE BLOCK	ABUTMENTS ON CONCRETE SPRE	AD FOOTING FOUNDATION
BENTS:	NOT APPLICABLE		
PIERS:	MASONRY OR CONCRETE BLOCK	PIER ON CONCRETE SPREAD FOO	TING FOUNDATION
		SCOUR EVALUATION =	
	unknown foundations. Risk of sco icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection		[] BridgeWatch Alert	
	•	-	al Maintenance Personnel
		[] THP or Local Law En	forcement Personnel
		[] Other:	
Things to c	heck on a bridge during floods	<u>s:</u>	
1. C 2. C	movement - horizontally as well heck displacement / deflection check for plumb of piers or being the for embankment erosion	n along curb line, both bridg	e rails and outer edge of bridge deck.
[] - Chec	k for drift build-up on piers or	bents	
	k pier exposure, if possible, ar	• • •	
[] - Revie	ew the latest bridge inspection	report versus current field c	onditions
<u>lf Closure is</u>	recommended:		
Coun temp	nty or City Maintenance Person	nel. Use Barricade Tape, tra	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State	maintained)
	(2) City or County Highwa	y Maintenance Official (if br	ridge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance idge on the selected detour route shall be checked	
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR'S OFFICE	(423) 663-2000	
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 663-3831	
COUNTY SHERIFF'S OFFICE	(423) 663-2245	
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 		
COMMENTS:		
Suggested List of Equipment to conduct the Inspect Latest Bridge Inspection Report	ion:	
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	ape printed with the following message:	
SAFETY HAZARD KEEP	AWAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19