HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 760A2430001

BRIDGE OWNER: SCOTT COUNTY

ROAD NAME: WOLF CREEK RD

CROSSING: BLACK WOLF CREEK

LATITUDE:: N 36.28537 DEGREES

LONGITUDE: W 84.56022 DEGREES

COUNTY: SCOTT
ROUTE: 0A246
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.06
YEAR BUILT: 1975

		TYPE OF SUPERS	STRUCTURE -		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR			NOT APPLICABLE	
		TYPE OF SUBST	RUCTURE -		
	CONCRETE BOX TYPE ON UNKNOW	N FOUNDATION			
BENTS:	NOT APPLICABLE				
PIERS:	NOT APPLICABLE				
		SCOUR EVAL	UATION -		
	nknown foundations. Risk of scor cant flood events. Monitor bridge			bridge shall be monitored for distress termeasures.	
		INSPECTION PRO	OCEDURES -		
What Initiated the Call-out Inspection? [] BridgeWatch Alert					
		[] TDOT Di	strict or Loca	al Maintenance Personnel	
		[] THP or L	ocal Law Enf	forcement Personnel	
		[] Other: _			
Things to cl	neck on a bridge during floods	L			
1. C 2. C	heck for plumb of piers or ben	along curb line	e, both bridge	e rails and outer edge of bridge deck.	
[] - Check for embankment erosion [] - Check for drift build-up on piers or bents					
	• •		rovious inspe	action	
 Check pier exposure, if possible, and compare to previous inspection Review the latest bridge inspection report versus current field conditions 					
[] - Kevie	w the latest bridge inspection	eport versus c	urrent neia c	unditions	
f Closure is	recommended:				
1 - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.					
[] - Conta	- Contact: (1) District Maintenance Supervisor (if bridge is State maintained)				
	(2) City or County Highway	Maintenance (Official (if br	idge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or loca	I law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer			
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.				

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route. 	District maintenance or local highway maintenance ge on the selected detour route shall be checked				
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.				
CONTACT PERSONNEL:	TELEPHONE NUMBER:				
COUNTY MAYOR'S OFFICE	(423) 663-2000				
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 663-3831				
COUNTY SHERIFF'S OFFICE	(423) 663-2245				
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 					
COMMENTS:					
Suggested List of Equipment to conduct the Inspection	<u>in:</u>				
Latest Bridge Inspection Report					
Scour POA Report with the above Checklist					
Bridge Design Plans, if available					
Tape measure with weight Plumb bob					
Range Pole					
A 1000 Foot Roll of yellow Polyethylene Barricade Tap	be printed with the following message:				
SAFETY HAZARD KEEP A					

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape