HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: SEQUATCHIE

BRIDGE ID NUMBER: 77022290001

BRIDGE OWNER: SEQUATCHIE COUNTY
ROAD NAME: COOKSTON RD
CROSSING: WOODCOCK CREEK
LATITUDE:: N 35.32216 DEGREES
LONGITUDE: W 85.43390 DEGREES

ROUTE: 02229

SPECIAL CASE: 0

COUNTY SEQUENCE: 1

LOG MILE: 1.43

YEAR BUILT: 1940

TYPE OF SUPERSTRUCTURE = MAIN SPAN-**CONCRETE - TEE BEAM** APPR. SPAN: NOT APPLICABLE TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE SPILL THROUGH ABUTMENT ON UNKNOWN FOUNDATION BENTS: CONCRETE COLUMN TWO POST BENT ON UNKNOWN FOUNDATION PIERS: **NOT APPLICABLE** SCOUR EVALUATION Bridge has unknown foundations. Risk of scour cannot be determined. The bridge shall be monitored for distress during significant flood events. Monitor bridge in lieu of installing scour countermeasures. **INSPECTION PROCEDURES** [] BridgeWatch Alert What Initiated the Call-out Inspection? [1 TDOT District or Local Maintenance Personnel [] THP or Local Law Enforcement Personnel [] Other: Things to check on a bridge during floods: [] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [] - Check for embankment erosion [] - Check for drift build-up on piers or bents [] - Check pier exposure, if possible, and compare to previous inspection [] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained) (2) City or County Highway Maintenance Official (if bridge is not State maintained)

PUBLICATION DATE

(3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate

[] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

(4) TDOT Regional Bridge Engineer

by a TDOT bridge inspection team.

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ate District maintenance or local highway maintenance oridge on the selected detour route shall be checked
[] - The bridge can be re-opened only after a TD units and they are determined to be structure.	OT bridge inspection team checks the substructure ally stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(423) 949-3479
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 949-2135
COUNTY SHERIFF'S OFFICE	(423) 949-2193
as appropriate, photographs of the bridge an	pection to BridgeWatch scour monitoring system. the inspection, a brief summary of findings and, id stream channel measurements. If significant be copied to Bridge Inspection Headquarters.
COMMENTS:	
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report	ction:
Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	Tone printed with the following manages:
A 1000 Foot Roll of yellow Polyethylene Barricade SAFFTY HAZARD KEF	
SAFFIT DAZARIJAFE	C AVVA I

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)