HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 780A3240001

BRIDGE OWNER: SEVIER COUNTY

ROAD NAME: HARRISBURG RD

CROSSING: EAST FORK

LATITUDE:: N 35.86105 DEGREES LONGITUDE: W 83.48238 DEGREES

COUNTY: SEVIER
ROUTE: 0A324
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.58
YEAR BUILT: 1875

		TYPE OF SUPERSTRUCTURE =		
MAIN SPAN:	WOOD OR TIMBER - TRUSS - THRU	APPR. SPAN:	STEEL - STRINGER/MULTI-BEAM OR GIRDER	
A DUITA (ENITO		TYPE OF SUBSTRUCTURE =		
ABUTMENTS:		IT ON CONCRETE SPREAD FOOTII	NG FOUNDATION	
BENTS:	NOT APPLICABLE	IED ON MACONDY FOOTING FOUN	UD ATION	
PIERS:	MASONRY OR CONCRETE BLOCK P	IER ON MASONRY FOOTING FOOT	NDATION	
		SCOUR EVALUATION -		
	unknown foundations. Risk of scou icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.	
		INSPECTION PROCEDURES =		
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert		
·			al Maintenance Personnel	
		[] THP or Local Law Enf	forcement Personnel	
		[] Other:		
Things to c	heck on a bridge during floods:			
1. C 2. C	Check for plumb of piers or ben	along curb line, both bridge	e rails and outer edge of bridge deck.	
[] - Check for embankment erosion				
	k for drift build-up on piers or b			
	k pier exposure, if possible, and			
[] - Revie	ew the latest bridge inspection i	eport versus current field co	onditions	
If Closure is	recommended:			
[] - Stay a Coun temp	at bridge with vehicle pulled ac ity or City Maintenance Personi	nel. Use Barricade Tape, traf	eured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may	
[] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)				
	(2) City or County Highway	Maintenance Official (if br	idge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any prior to signing the detour route.	bridge on the selected detour route shall be checked		
	ge can be re-opened only after a TDOT bridge inspection team checks the substructure I they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(865) 453-6136		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(865) 453-3452		
COUNTY SHERIFF'S OFFICE	(865) 453-4668		
as appropriate, photographs of the bridge a	the inspection, a brief summary of findings and, and stream channel measurements. If significant be copied to Bridge Inspection Headquarters.		
Suggested List of Equipment to conduct the Inspe	ection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade			
SAFETY HAZARD KEI	EP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)