HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 780B0720001

BRIDGE OWNER: CITY OF SEVIERVILLE

ROAD NAME: RAIL ROAD ST CROSSING: MIDDLE CREEK

LATITUDE:: N 35.86285 DEGREES
LONGITUDE: W 83.55552 DEGREES

COUNTY: SEVIER
ROUTE: 06028
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.20
YEAR BUILT: 1940

		TYPE OF SUPERSTRUCTURE =		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OF		NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE -		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON UNKNOWN FOUNDATION		
BENTS:	NOT APPLICABLE			
PIERS:	CONCRETE HAMMERHEAD PIER ON	I UNKNOWN FOUNDATION		
		SCOUR EVALUATION =		
	unknown foundations. Risk of sco ficant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.	
		INSPECTION PROCEDURES =		
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert		
		[] TDOT District or Loca	ıl Maintenance Personnel	
		[] THP or Local Law Enf	orcement Personnel	
		[] Other:		
Things to c	<u>heck on a bridge during floods</u>	<u>.</u> <u>.</u>		
[] - Span	movement - horizontally as we	ell as vertically		
1. 0	Check displacement / deflection	along curb line, both bridge	e rails and outer edge of bridge deck.	
2. 0	Check for plumb of piers or ber	its.		
[] - Chec	k for embankment erosion			
[] - Chec	k for drift build-up on piers or l	pents		
[] - Chec	k pier exposure, if possible, an	d compare to previous inspe	ection	
[] - Review the latest bridge inspection report versus current field conditions				
K 01				
	recommended:			
Coun temp	1 - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.			
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State	maintained)	
	(2) City or County Highway	Maintenance Official (if br	idge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	he Bridge should remain closed until the water recedes and a daylight visual inspection is made y a TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



officials in establishing a detour route. Any bri prior to signing the detour route.	The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route. The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure		
units and they are determined to be structurall			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
CITY MAYOR'S OFFICE	(865) 453-5504		
CITY ENGINEER'S OFFICE	(865) 453-5504		
POLICE OFFICE	(865) 453-5506		
PUBLIC WORKS DIRECTOR	(865) 429-4567		
The report shall include the date and time of th as appropriate, photographs of the bridge and scouring has occurred, the report shall also be	stream channel measurements. If significant copied to Bridge Inspection Headquarters.		
Suggested List of Equipment to conduct the Inspect	on:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	pe printed with the following message:		
SAFETY HAZARD KEEP	AWAY		

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)