HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 79014500015

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: SHELBY DR
CROSSING: BRANCH

LATITUDE:: N 35.02061 DEGREES
LONGITUDE: W 89.72897 DEGREES

COUNTY: SHELBY
ROUTE: SR175
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 21.57

LON	NGITUDE: W 89.72897 DEGREES	YEAR BUILT: 1948
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE STUB ABUTMENT ON C	ONCRETE PILE FOUNDATION
BENTS:	CONCRETE PILE BENT ON PILE FO	UNDATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
event. Deter	ioration of channel protection or	have been installed to reduce the risk of bridge failure during a flood riprap should be reported to TDOT for assessment. Rip-rap protection has minor repairs to the protection system are needed.
		INSPECTION PROCEDURES ————————————————————————————————————
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
Things to c	heck on a bridge during floods	s:
	movement - horizontally as w	
	•	n along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	
	k for embankment erosion	
	k for drift build-up on piers or	bents
	• •	nd compare to previous inspection
		report versus current field conditions
<u>If Closure is</u>	recommended:	
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, anel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	supervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed u TDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any bridg prior to signing the detour route.	ge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
The report shall include the date and time of the i as appropriate, photographs of the bridge and str scouring has occurred, the report shall also be co	ream channel measurements. If significant opied to Bridge Inspection Headquarters.		
Suggested List of Equipment to conduct the Inspection	<u>ı:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape			
SAFETY HAZARD KEEP AV	NAY		

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape