## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



BRIDGE ID NUMBER: 79014640001 BRIDGE OWNER: SHELBY COUNTY ROAD NAME: WEST UNION RD CROSSING: BEAR CREEK

> LATITUDE" N 35 36792 DEGREES

COUNTY: SHELBY ROUTE: 01464 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 102

	NGITUDE: W 89.94189 DEGREE		
LOI	101100E. 11 09.94109 DEGREE	TEAR BOILT. 1900	
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE CONTI BEAM OR GIRDERS - SINGLE OR S		
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	CONCRETE PILE FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE SOLID SHAFT PIER ON	I CONCRETE PILE FOUNDATION	
		SCOUR EVALUATION	
event. Deter	ioration of channel protection or	s have been installed to reduce the risk of bridge failure during a flood riprap should be reported to TDOT for assessment. Rip-rap protection has minor repairs to the protection system are needed.	
		INSPECTION PROCEDURES	
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert	
		[ ] TDOT District or Local Maintenance Personnel	
		[ ] THP or Local Law Enforcement Personnel	
		[ ] Other:	
Things to o	hook on a bridge during fleed	o.	
_	heck on a bridge during flood		
	movement - horizontally as w	•	
	•	n along curb line, both bridge rails and outer edge of bridge deck.	
	Check for plumb of piers or be k for embankment erosion	nts.	
	k for drift build-up on piers or	honte	
		nd compare to previous inspection	
	• • • • • •	report versus current field conditions	
[ ] - KCVIC	w the latest bridge mapeener	report versus current neid conditions	
<u>If Closure is</u>	recommended:		
Coun temp	nty or City Maintenance Person	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may	
[ ] - Conta	act: (1) District Maintenance \$	Supervisor ( if bridge is State maintained )	
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )	
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	e Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made a TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



<ul> <li>The bridge inspection team will work with State officials in establishing a detour route. Any bridge prior to signing the detour route.</li> </ul>	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
[ ] - The bridge can be re-opened only after a TDOT be units and they are determined to be structurally			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(901) 545-4500		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(901) 379-4414		
PUBLIC WORKS DIRECTOR	(901) 545-4266		
COUNTY SHERIFF'S OFFICE	(901) 545-5500		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and,         as appropriate, photographs of the bridge and stream channel measurements. If significant         scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.</li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection  Latest Bridge Inspection Report	<u>n:</u>		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape			

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

**TDOT radio directory (State Personnel only)**