HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 79028210005
BRIDGE OWNER: CITY OF MEMPHIS
ROAD NAME: N HOLLYWOOD ST
CROSSING: WOLF RIVER

LATITUDE:: N 35.18725 DEGREES
LONGITUDE: W 89.97564 DEGREES

COUNTY: SHELBY
ROUTE: 02821
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 5.02
YEAR BUILT: 1965

LON	NGITUDE: W 89.97564 DEGREES			YEAR BUILT: 1965	
		TYPE OF SUPERS	STRUCTURE -		
MAIN SPAN:	STEEL CONTINUOUS - STRINGER/N GIRDER	IULTI-BEAM OR	APPR. SPAN:	PRESTRESSED CONCRETE - STRINGER/MULTI- BEAM OR GIRDER	
		TYPE OF SUBST	RUCTURE =		
ABUTMENTS:	CONCRETE STUB ABUTMENT ON C	ONCRETE PILE FO	UNDATION		
BENTS:	CONCRETE COLUMN FOUR OR MO	RE POST BENT ON	CONCRETE PIL	LE FOUNDATION	
PIERS:	CONCRETE HAMMERHEAD PIER ON CONCRETE PILE FOUNDATION				
		SCOUR EVAL	UATION =		
	our critical; bridge foundations de stalled and is in fair condition. So			culated scour conditions. Rip-rap protection tion system are needed.	
		INSPECTION PRO	OCEDURES -		
What Initiated the Call-out Inspection?		[] BridgeW	atch Alert		
				al Maintenance Personnel	
				forcement Personnel	
		[] Other: _			
1. C 2. C [] - Chec [] - Chec	movement - horizontally as we Check displacement / deflection Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, and ew the latest bridge inspection	n along curb lind nts. bents nd compare to p	revious inspe		
<u>If Closure is</u>	recommended:				
Coun temp	nty or City Maintenance Person	nel. Use Barrica	ide Tape, traf	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may	
[] - Conta	act: (1) District Maintenance S	upervisor (if b	ridge is State	maintained)	
	(2) City or County Highwa	y Maintenance (Official (if br	ridge is not State maintained)	
	(3) Tennessee Highway Pa	atrol and/or loca	I law enforce	ement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer			
	The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.				

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	State District maintenance or local highway maintenance bridge on the selected detour route shall be checked				
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.				
CONTACT PERSONNEL:	TELEPHONE NUMBER:				
CITY MAYOR'S OFFICE	(901) 576-6007				
CITY ENGINEER'S OFFICE	(901) 576-6902				
PUBLIC WORKS DIRECTOR	(901) 576-7109				
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.					
COMMENTS:					
Suggested List of Equipment to conduct the Insp Latest Bridge Inspection Report	ection:				
Scour POA Report with the above Checklist					
Bridge Design Plans, if available					
Tape measure with weight					
Plumb bob					
Range Pole					
A 1000 Foot Roll of yellow Polyethylene Barricade	e Tape printed with the following message:				
CAEETV HAZADD VE	ED AWAY				

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24