HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 79028700003
BRIDGE OWNER: CITY OF MEMPHIS
ROAD NAME: AMERICAN WAY
CROSSING: JOHNS CREEK

LATITUDE:: N 35.07650 DEGREES

ROUTE: 05029
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 3.53
YEAR BUILT: 1975

COUNTY: SHELBY

LON	IGITUDE: W 89.89208 DEGREES	YEAR BUILT: 1975	
		TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	PRESTRESSED CONCRETE CONTI BEAM OR GIRDERS - SINGLE OR S		
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	TMENTS: CONCRETE FULL HEIGHT ABUTMENT ON CONCRETE PILE FOUNDATION		
BENTS:	ENTS: CONCRETE COLUMN FOUR OR MORE POST BENT ON PILE FOUNDATION		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
		our cannot be determined. The bridge shall be monitored for distress scour countermeasure protective system has been installed.	
		INSPECTION PROCEDURES ————————————————————————————————————	
What Initiated the Call-out Inspection		[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
[] - Span 1. C 2. C [] - Chec [] - Chec [] - Revie	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, and the latest bridge inspection	ell as vertically n along curb line, both bridge rails and outer edge of bridge deck. nts.	
<u>If Closure is</u>	recommended:		
Coun temp	ty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, inel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may	
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with Stat officials in establishing a detour route. Any bri prior to signing the detour route. 	e District maintenance or local highway maintenance dge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
CITY MAYOR'S OFFICE	(901) 576-6007		
CITY ENGINEER'S OFFICE	(901) 576-6902		
PUBLIC WORKS DIRECTOR	(901) 576-7109		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Inspecti	on:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	pe printed with the following message:		
SAFETY HAZARD KEEP	AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24