HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 79028780007
BRIDGE OWNER: CITY OF MEMPHIS
ROAD NAME: RALEIGH-LAGRANGE RD
CROSSING: HURRICANE CREEK
LATITUDE:: N 35.18719 DEGREES

COUNTY: SHELBY
ROUTE: 02878
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 4.52
YEAR BUILT: 1998

LON	IGITUDE: W 89.88689 DEGREES	YEAR BUILT: 1998	
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE - BOX E GIRDERS - MULTIPLE	EEAM OR APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON C	ONCRETE PILE FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
		ur cannot be determined. The bridge shall be monitored for distress in lieu of installing scour countermeasures.	
		INSPECTION PROCEDURES ————————————————————————————————————	
What Initiated the Call-out Inspection		[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
[] - Span 1. C 2. C [] - Chec [] - Chec	Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, an	ell as vertically n along curb line, both bridge rails and outer edge of bridge deck. nts.	
If Closure is	recommended:		
Coun temp	ity or City Maintenance Person	eross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may	
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



officials in		ate District maintenance or local highway maintenance ridge on the selected detour route shall be checked	
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PE	ERSONNEL:	TELEPHONE NUMBER:	
CITY MAYOR	'S OFFICE	(901) 576-6007	
CITY ENGINE	EER'S OFFICE	(901) 576-6902	
PUBLIC WOF	RKS DIRECTOR	(901) 576-7109	
The report as appropri] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
Suggested List o	of Equipment to conduct the Inspec	etion:	
Latest Bridge Ins	spection Report		
•	ort with the above Checklist		
Bridge Design Pl			
Tape measure wi	ith weight		
Plumb bob			
Range Pole	of wellow Debugths love Demise de 3	Fanna mainta dunith tha fallannin managara	
A 1000 FOOt ROII	SAFETY HAZARD KEE	Tape printed with the following message:	
	SAFEIT MAZAKU KEE	T AVVA I	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24