HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 790A0210003

BRIDGE OWNER: STATE OF TENNESSEE ROAD NAME: S FORREST RD

CROSSING: BRANCH

LATITUDE" N 35 32506 DEGREES

COUNTY: SHELBY ROUTE: 0A035 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 2.51

	NITIODE N 33.32306 DEGREE	
LON	NGITUDE: W 90.05019 DEGREES	S YEAR BUILT: 1977
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	PRESTRESSED CONCRETE - BOX GIRDERS - MULTIPLE	BEAM OR APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	CONCRETE PILE FOUNDATION
BENTS:	CONCRETE PILE BENT ON PILE FO	OUNDATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
Bridge is see	our critical but countermoscurer	s have been installed to reduce the risk of bridge failure during a flood
event. Deter		riprap should be reported to TDOT for assessment. A permanent scour
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
1. 0 2. 0 [] - Chec [] - Chec	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or	on along curb line, both bridge rails and outer edge of bridge deck.
[] - Revie	w the latest bridge inspection	n report versus current field conditions
lf Closure is	recommended:	
[] - Stay a Countemp	at bridge with vehicle pulled a nty or City Maintenance Perso	across road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may.
[] - Conta	ct: (1) District Maintenance Supervisor (if bridge is State maintained)	
	(2) City or County Highwa	ay Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	Patrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	e Engineer
	Bridge should remain closed บ TDOT bridge inspection team.	until the water recedes and a daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



] - The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.			
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
 Summarize and submit findings from the inspection. The report shall include the date and time of the in as appropriate, photographs of the bridge and stresscouring has occurred, the report shall also be contained. 	nspection, a brief summary of findings and, eam channel measurements. If significant		
COMMENTS:			
Suggested List of Equipment to conduct the Inspection:	<u> </u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape	printed with the following message:		
SAFETY HAZARD KEEP AW			
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			
Traffic Cones - Minimum of four (4)			

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)