HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 790A6730001
BRIDGE OWNER: SHELBY COUNTY
ROAD NAME: GEORGE R JAMES RD

CROSSING: BRANCH

LATITUDE:: N 35.18211 DEGREES LONGITUDE: W 89.65328 DEGREES

COUNTY: SHELBY
ROUTE: 0D994
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.53
YEAR BUILT: 1972

201	1011052. 11 03.00020 520 11220	TEAUCOGET. 1012	
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON O	CONCRETE PILE FOUNDATION	
BENTS:	CONCRETE COLUMN FOUR OR MC	ORE POST BENT ON PILE FOUNDATION	
PIERS:	NOT APPLICABLE		
		COOUR EVALUATION	
D.1		SCOUR EVALUATION	
		etermined to be unstable for calculated scour conditions. Rip-rap protection me minor repairs to the protection system are needed.	
		INSPECTION PROCEDURES ————————————————————————————————————	
What Initiat	ted the Call-out Inspection?	[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
Things to c	heck on a bridge during floods	<u>s:</u>	
[] - Snan	movement - horizontally as w	ell as vertically	
	-	n along curb line, both bridge rails and outer edge of bridge deck.	
	Check for plumb of piers or be		
	k for embankment erosion		
	k for drift build-up on piers or	bents	
		nd compare to previous inspection	
		report versus current field conditions	
[]	on the latest shage meposion.	Toport volcue dull'one notal domainone	
If Closure is	s recommended:		
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may	
		Supervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer Engineer	
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any bridg prior to signing the detour route.	ge on the selected detour route shall be checked		
	bridge can be re-opened only after a TDOT bridge inspection team checks the substructure ts and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(901) 545-4500		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(901) 379-4414		
PUBLIC WORKS DIRECTOR	(901) 545-4266		
COUNTY SHERIFF'S OFFICE	(901) 545-5500		
as appropriate, photographs of the bridge and str scouring has occurred, the report shall also be co	opied to Bridge Inspection Headquarters.		
Suggested List of Equipment to conduct the Inspection	<u>n:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape	a printed with the following massage:		
SAFETY HAZARD KEEP A			
A Barricade Tape Dispenser with serrated cutter			

PUBLICATION DATE

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone