## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 790M0100003						COUNTY:	SHELBY	
BRIDGE OWNER: CITY OF MEMPHIS			HIS			ROUTE:	04196	
ROAD NAME: WEAVER RD					SPECIAL CASE:	0		
CROSSING: CYRESS CREEK		к			COUNTY SEQUENCE:	1		
LATITUDE:: N		N 35.06150	DEGREES			LOG MILE:	3.53	
LONG	GITUDE: V	V 90.09256	DEGREES			YEAR BUILT:	1969	
				TYPE OF SUPERS	TRUCTURE -			
MAIN SPAN:	STEEL - S	TRINGER/MUI	TI-BEAM OR	GIRDER	APPR. SPAN:	NOT APPLICABLE		
				TYPE OF SUBST				
ABUTMENTS:	NTS: CONCRETE STUB ABUTMENT ON CONCRETE PILE FOUNDATION							
BENTS:	ENTS: CONCRETE COLUMN FOUR OR MORE POST BENT ON PILE FOUNDATION							
PIERS:	NOT APPLICABLE							
				SCOUR EVAL	JATION -			
•				r cannot be dete in lieu of installir		bridge shall be monitored termeasures.	for distress	
				INSPECTION PRO	CEDURES -			
What Initiate	ed the Ca	ll-out Inspe	ction?	[] BridgeWa	atch Alert			
				[ ] TDOT Dis	strict or Loca	I Maintenance Personne	el	

- [] THP or Local Law Enforcement Personnel
- [ ] Other: \_\_\_\_

## Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
  - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.
  - 2. Check for plumb of piers or bents.
- [ ] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [ ] Review the latest bridge inspection report versus current field conditions

## If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [ ] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
  - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
  - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
  - (4) TDOT Regional Bridge Engineer
- [] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

PUBLICATION DATE

07-Nov-24

BRIDGE ID 790M0100003



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	TELEPHONE NUMBER:
CITY MAYOR'S OFFICE	(901) 576-6007
CITY ENGINEER'S OFFICE	(901) 576-6902
PUBLIC WORKS DIRECTOR	(901) 576-7109

[ ] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

COMMENTS: \_\_\_\_\_

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

**Range Pole** 

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

## SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)

PUBLICATION DATE