# HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 79S80740009				COUNTY:	SHELBY	
BRIDGE OWNER: SHELBY COUNTY				ROUTE:	05757	
ROAD NAME: COLLIERVILLE-ARLINGTON RD				SPECIAL CASE:	0	
CR	OSSING: OVERFLOW			COUNTY SEQUENCE:	1	
LA	TITUDE:: N 35.08969 D	DEGREES		LOG MILE:	3.12	
LON	GITUDE: W 89.65111 D	DEGREES		YEAR BUILT:	1959	
TYPE OF SUPERSTRUCTURE						
MAIN SPAN:	STEEL - STRINGER/MULTI	-BEAM OR GIRDER	APPR. SPAN:	NOT APPLICABLE		
TYPE OF SUBSTRUCTURE						
ABUTMENTS:	CONCRETE STUB ABUTM	ENT ON CONCRETE PILE F	OUNDATION			
BENTS:	CONCRETE PILE BENT ON	N PILE FOUNDATION				
PIERS:	NOT APPLICABLE					
		SCOUR EVA				
-	nknown foundations. Ris cant flood events. Monite			oridge shall be monitored ermeasures.	for distress	
		INSPECTION P	ROCEDURES -			
What Initiate	ed the Call-out Inspect	ion? [] Bridge	Natch Alert			

- [ ] TDOT District or Local Maintenance Personnel
- [] THP or Local Law Enforcement Personnel
- [ ] Other: \_\_\_\_

## Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
  - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.
  - 2. Check for plumb of piers or bents.
- [ ] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [ ] Review the latest bridge inspection report versus current field conditions

## If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [ ] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
  - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
  - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
  - (4) TDOT Regional Bridge Engineer
- [] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

PUBLICATION DATE

07-Nov-24

BRIDGE ID 79S80740009



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(901) 545-4500
HWY. CHIEF ADMINISTRATOR'S OFFICE	(901) 379-4414
PUBLIC WORKS DIRECTOR	(901) 545-4266
COUNTY SHERIFF'S OFFICE	(901) 545-5500

[ ] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

#### COMMENTS:

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

**Range Pole** 

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

#### SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

**TDOT radio directory (State Personnel only)** 

PUBLICATION DATE

07-Nov-24