Rev. 07-24-15		HIGHWAY BRIDGE PLAN OF ACTION		T	N TDOT Department of Transportation
BRIDGE OWI	BER: 79S81050001 NER: Shelby County Ame: Fite Road			COUNTY: \$ ROUTE: (SPECIAL CASE: (05459
CROSS LATITU	BING: BIG CREEK CANAL JDE:: N 35.28028 DE	EGREES EGREES		COUNTY SEQUENCE: LOG MILE: YEAR BUILT:	1 1.36
		TYPE OF SUPERS			
	EEL CONTINUOUS - STR RDER	NGER/MULTI-BEAM OR	APPR. SPAN: NO	T APPLICABLE	
		TYPE OF SUBST			
ABUTMENTS: CO	NCRETE STUB ABUTME	NT ON CONCRETE PILE FO	JNDATION		
BENTS: CO	NCRETE COLUMN FOUR	OR MORE POST BENT ON	PILE FOUNDATION		
PIERS: CO	NCRETE SOLID SHAFT F		OUNDATION		
		SCOUR EVAL			
		<pre>< of scour cannot be dete r bridge in lieu of installir</pre>			or distress
		INSPECTION PRO	CEDURES		

What	Initiated	the	Call-out	Insp	ection?
	minutou		oun out	mop	000000

- [] BridgeWatch Alert
 - [] TDOT District or Local Maintenance Personnel
 - [] THP or Local Law Enforcement Personnel
 - [] Other: ____

Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
 - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.
 - 2. Check for plumb of piers or bents.
- [] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [] Review the latest bridge inspection report versus current field conditions

If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
 - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
 - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
 - (4) TDOT Regional Bridge Engineer
- [] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

PUBLICATIO	N DATE
------------	--------

07-Nov-24



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(901) 545-4500
HWY. CHIEF ADMINISTRATOR'S OFFICE	(901) 379-4414
PUBLIC WORKS DIRECTOR	(901) 545-4266
COUNTY SHERIFF'S OFFICE	(901) 545-5500

[] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

COMMENTS: _

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

Range Pole

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)

PUBLICATION DATE

07-Nov-24