## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 79SR0010039

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: US70/79

CROSSING: LOOSAHATCHIE RIVER
LATITUDE:: N 35.31053 DEGREES
LONGITUDE: W 89.63964 DEGREES

ROUTE: SR001
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 30.36

COUNTY: SHELBY

LON	NGITUDE: W 89.63964 DEGREES	YEAR BUILT: 1925	
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE - BOX E GIRDERS - MULTIPLE	EAM OR APPR. SPAN: CONCRETE - TEE BEAM	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON C	ONCRETE PILE FOUNDATION	
BENTS:	CONCRETE PILE BENT ON PILE FO	JNDATION	
PIERS:	CONCRETE SOLID SHAFT PIER ON	TIMBER PILE FOUNDATION	
		SCOUR EVALUATION	
	our critical; bridge foundations de stalled and is in good condition.	termined to be unstable for calculated scour conditions. Rip-rap protection	
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
	•	[ ] TDOT District or Local Maintenance Personnel	
		THP or Local Law Enforcement Personnel	
		[ ] Other:	
1. 0 2. 0 [ ] - Chec [ ] - Chec [ ] - Chec	Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, ar	along curb line, both bridge rails and outer edge of bridge deck. ts.	
lf Closure is	recommended:		
Coun temp	ity or City Maintenance Person	ross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as sts to stay off of the bridge until such time as the bridge may	
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State maintained )	
	(2) City or County Highwa	Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	tate District maintenance or local highway maintenance bridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspe	ection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:		
SAFETY HAZARD KEE	EP AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19