## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 79SR0150001

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: STAGE RD

CROSSING: W. FK. FLETCHER CREEK
LATITUDE:: N 35.20372 DEGREES
LONGITUDE: W 89.82128 DEGREES

ROUTE: SR015
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 5.83

COUNTY: SHELBY

LON	NGITUDE: W 89.82128 DEGREES	<b>;</b>	YEAR BUILT: 1983
MAIN SPAN:	PRESTRESSED CONCRETE CONTI	TYPE OF SUPERSTRUCTURE = NUOUS - APPR. SPAN:	NOT APPLICABLE
WAIN SPAN.	STRINGER/MULTI-BEAM OR GIRDE		NOT AFFEIGABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON (	CONCRETE PILE FOUNDATION	
BENTS:	CONCRETE COLUMN FOUR OR MO	RE POST BENT ON CONCRETE PIL	E FOUNDATION
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
Bridge is sco	our critical: bridge foundations de	etermined to be unstable for cal	culated scour conditions. Rip-rap protection
	stalled but is in poor condition. S		
		- INSPECTION PROCEDURES -	
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert	
vviidt iiiitidt	od tilo odii odi iliopootioii i	•	al Maintenance Personnel
		[ ] THP or Local Law Enf	
Things to c	heck on a bridge during flood	<u>3:</u>	
[ ] - Span	movement - horizontally as w	ell as vertically	
1. 0	Check displacement / deflectio	n along curb line, both bridge	e rails and outer edge of bridge deck.
2. 0	Check for plumb of piers or be	nts.	
	k for embankment erosion		
	k for drift build-up on piers or		
	k pier exposure, if possible, a	• • •	
[ ] - Revie	ew the latest bridge inspection	report versus current field c	onditions
If Closure is	recommended:		
		cross road until bridge is sec	cured and properly closed by District,
Coun	ity or City Maintenance Persor	nnel. Use Barricade Tape, traf	ffic cones and/or traffic flares as
			until such time as the bridge may
-	operly closed and barricaded. act: (1) District Maintenance S		maintained \
[ ] - Conta		•	ridge is not State maintained)
	``	· ·	ement Officers as appropriate
	(4) TDOT Regional Bridge		mont officers as appropriate
[ ] - The F	` '		davlight visual inspection is made
	<ul> <li>The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.</li> </ul>		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ith State District maintenance or local highway maintenance Any bridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the In	nspection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
	cade Tape printed with the following message:		
SAFETY HAZARD	KEEP AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24