## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 79SR3880001

BRIDGE OWNER: **STATE OF TENNESSEE** 

ROAD NAME: N WATKINS ST

CROSSING: LOOSAHATCHIE RIVER
LATITUDE:: N 35.25308 DEGREES
LONGITUDE: W 90.02561 DEGREES

ROUTE: SR388
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.36

COUNTY: SHELBY

LON	NGITUDE: <b>W 90.02561 D</b>	EGREES			YEAR BUILT: 1970
		т	YPE OF SUPER	STRUCTURE -	
MAIN SPAN:	STEEL CONTINUOUS - STE GIRDER	RINGER/MUL	TI-BEAM OR	APPR. SPAN:	STEEL - STRINGER/MULTI-BEAM OR GIRDER
			TYPE OF SUBS	TRUCTURE -	
ABUTMENTS:	CONCRETE STUB ABUTME	ENT ON CON	ICRETE PILE FO	DUNDATION	
BENTS: CONCRETE COLUMN TWO POST BENT ON CONCRETE PILE FOUNDATION					TION
PIERS:	CONCRETE HAMMERHEAD	PIER ON C	ONCRETE PILE	FOUNDATION	
			SCOUR EVAI	_UATION =	
	our critical; bridge founda stalled but is in poor cond		mined to be u	instable for cal	culated scour conditions. Rip-rap protection on system are needed.
		ı	NSPECTION PR	OCEDURES -	
What Initiat	ed the Call-out Inspecti	on?	[ ] BridgeV	/atch Alert	
	•		D TOOT D	istrict or Loca	al Maintenance Personnel
			[ ] THP or I	Local Law Enf	forcement Personnel
			[ ] Other:		
1. 0 2. 0 [ ] - Chec [ ] - Chec	movement - horizontal Check displacement / de Check for plumb of piers ok for embankment eros ok for drift build-up on p ok pier exposure, if poss ow the latest bridge insp	eflection a s or bents ion iers or be sible, and	long curb lin nts compare to p	previous inspe	
lf Closure is	recommended:				
Cour temp	nty or City Maintenance	Personne motorist	l. Use Barric	ade Tape, traf	eured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Mainter	ance Sup	ervisor ( if b	ridge is State	maintained )
	(2) City or County	Highway N	/laintenance	Official ( if br	idge is not State maintained )
	(3) Tennessee High	nway Patr	ol and/or loca	al law enforce	ment Officers as appropriate
	(4) TDOT Regional	Bridge E	ngineer		
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.				

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ate District maintenance or local highway maintenance ridge on the selected detour route shall be checked					
	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>					
CONTACT PERSONNEL:	TELEPHONE NUMBER:					
REGION BRIDGE ENGINEER	(731) 234-9561					
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610					
TENNESSEE HIGHWAY PATROL	(901) 543-6256					
[ ] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.						
COMMENTS:						
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report	etion:					
Scour POA Report with the above Checklist						
Bridge Design Plans, if available						
Tape measure with weight						
Plumb bob						
Range Pole A 1000 Foot Roll of yellow Polyethylene Barricade T	Cano printed with the following message:					
SAFETY HAZARD KEE						
	. / 107/11					

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)