HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 81003470015

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: THE TRACE
CROSSING: HICKMAN CREEK

LATITUDE:: N 36.48112 DEGREES
LONGITUDE: W 87.88905 DEGREES

COUNTY: STEWART
ROUTE: SR461
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.08
YEAR BUILT: 1981

	10.1.032. II 01.0000 B201.220			12, 11, 120, 12, 12, 12, 12, 12, 12, 12, 12, 12, 12	
		TYPE OF SUF	PERSTRUCTURE -		
MAIN SPAN:	PRESTRESSED CONCRETE - BOX I GIRDERS - SINGLE OR SPREAD	BEAM OR	APPR. SPAN:	NOT APPLICABLE	
		TYPE OF SU	BSTRUCTURE -		
ABUTMENTS:	CONCRETE STUB ABUTMENT ON S	RETE STUB ABUTMENT ON STEEL PILE FOUNDATION			
BENTS:	NOT APPLICABLE				
PIERS:	CONCRETE SOLID SHAFT PIER ON CONCRETE SPREAD FOOTING FOUNDATION				
		SCOUR E	VALUATION -		
	unknown foundations. Risk of sco icant flood events. Monitor bridg			bridge shall be monitored for distress termeasures.	
		- INSPECTION	PROCEDURES -		
What Initiated the Call-out Inspection?		[] Bridg	eWatch Alert		
		[] TDO	Γ District or Loca	Il Maintenance Personnel	
		[] THP	or Local Law Enf	orcement Personnel	
		[] Othe	r:		
Things to c	heck on a bridge during floods	<u>s:</u>			
1. 0	movement - horizontally as w Check displacement / deflectio Check for plumb of piers or be	n along curb	-	e rails and outer edge of bridge deck.	
	k for embankment erosion	iits.			
	k for drift build-up on piers or	hants			
	k pier exposure, if possible, ar		o nrevious inspe	ection	
	ew the latest bridge inspection	-			
lf Closure is	recommended:				
[] - Stay a Coun temp	at bridge with vehicle pulled a ity or City Maintenance Persor	nnel. Use Bar rists to stay o	ricade Tape, traf	eured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may	
[] - Conta	ct: (1) District Maintenance Supervisor (if bridge is State maintained)				
	(2) City or County Highwa	y Maintenan	ce Official (if br	idge is not State maintained)	
	(3) Tennessee Highway P	atrol and/or l	ocal law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer			
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.				

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State Disordicials in establishing a detour route. Any bridge prior to signing the detour route. 			
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(615) 476-8860		
DISTRICT MAINTENANCE SUPERVISOR	(931) 205-6399		
TENNESSEE HIGHWAY PATROL	(615) 741-3181		
The report shall include the date and time of the ins as appropriate, photographs of the bridge and streat scouring has occurred, the report shall also be cop	am channel measurements. If significant ied to Bridge Inspection Headquarters.		
Suggested List of Equipment to conduct the Inspection:			
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape p	rinted with the following message:		
SAFETY HAZARD KEEP AWA			
A Barricade Tape Dispenser with serrated cutter	\ I		

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

A roll of Duct Tape