HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: STEWART

BRIDGE ID NUMBER: 81017990007
BRIDGE OWNER: STEWART COUNTY
ROAD NAME: ANTIOCH RD
CROSSING: BRANCH

LATITUDE:: N 36.58423 DEGREES LONGITUDE: W 87.86162 DEGREES

ROUTE: 01799
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.12

YEAR BUILT: 1975

		TYPE OF	SUPERSTRUCTURE -	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR		APPR. SPAN:	NOT APPLICABLE
		TYPE OF	SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN	NT ON CON	CRETE SPREAD FOOTI	NG FOUNDATION
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
		scou	R EVALUATION -	
event. Deteri		iprap shou	uld be reported to TD	the risk of bridge failure during a flood pOT for assessment. Rip-rap protection has system are needed.
		INSPECTI	ON PROCEDURES -	
What Initiate	ed the Call-out Inspection?	[] Br	idgeWatch Alert	
		[] TD	OT District or Loca	l Maintenance Personnel
		[] TH	IP or Local Law Enf	orcement Personnel
		[] Ot	her:	
[] - Span 1. C 2. C [] - Checl [] - Checl	check for plumb of piers or ben k for embankment erosion k for drift build-up on piers or k	ell as verti n along cu nts.	urb line, both bridge	e rails and outer edge of bridge deck.
	k pier exposure, if possible, and we the latest bridge inspection	-		
f Closure is	recommended:			
Coun tempo	ty or City Maintenance Person	nel. Use E	Barricade Tape, traf	ured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance Su	upervisor	(if bridge is State	maintained)
	(2) City or County Highway	/ Mainten	ance Official (if br	idge is not State maintained)
	(3) Tennessee Highway Pa	trol and/o	or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer		
	Bridge should remain closed un FDOT bridge inspection team.	ntil the wa	ater recedes and a d	laylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 232-3100		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 232-5968		
COUNTY SHERIFF'S OFFICE	(931) 232-8332		
- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspect	tion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta			
SAFETY HAZARD KEEP	PAWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24