HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 81018260001

BRIDGE OWNER: STEWART COUNTY

ROAD NAME: COX HOLLOW RD

CROSSING: STANDING ROCK CREEK

LATITUDE:: N 36.43218 DEGREES

COUNTY: STEWART
ROUTE: 0A467
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.54
YEAR BUILT: 1978

| LON | NGITUDE: W 87.96035 DEGREES | YEAR BUILT: 1978 |
|--|---|--|
| | | TYPE OF SUPERSTRUCTURE |
| MAIN SPAN: | PRESTRESSED CONCRETE - STRIN OR GIRDER | GER/MULTI-BEAM APPR. SPAN: NOT APPLICABLE |
| | | TYPE OF SUBSTRUCTURE |
| ABUTMENTS: | CONCRETE FULL HEIGHT ABUTME | NT ON CONCRETE SPREAD FOOTING FOUNDATION |
| BENTS: | NOT APPLICABLE | |
| PIERS: | CONCRETE HAMMERHEAD PIER OF | N CONCRETE SPREAD FOOTING FOUNDATION |
| | | |
| D : 1 · | | SCOUR EVALUATION ———————————————————————————————————— |
| | | that extensive scour has occurred at bridge foundations. Immediate action s. No scour countermeasures are installed but they are needed. |
| | | INSPECTION PROCEDURES |
| What Initiated the Call-out Inspection? | | [] BridgeWatch Alert |
| | • | [] TDOT District or Local Maintenance Personnel |
| | | [] THP or Local Law Enforcement Personnel |
| | | [] Other: |
| 1. 0 2. 0 [] - Chec [] - Chec | Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, an | n along curb line, both bridge rails and outer edge of bridge deck. nts. |
| <u>If Closure is</u> | recommended: | |
| Coun temp | ity or City Maintenance Person | cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may |
| [] - Conta | act: (1) District Maintenance S | upervisor (if bridge is State maintained) |
| | (2) City or County Highwa | y Maintenance Official (if bridge is not State maintained) |
| | (3) Tennessee Highway Pa | atrol and/or local law enforcement Officers as appropriate |
| | (4) TDOT Regional Bridge | Engineer |
| | Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team. | |

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



| The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route. | District maintenance or local highway maintenance ge on the selected detour route shall be checked | |
|---|--|--|
|] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. | | |
| CONTACT PERSONNEL: | TELEPHONE NUMBER: | |
| COUNTY MAYOR'S OFFICE | (931) 232-3100 | |
| HWY. CHIEF ADMINISTRATOR'S OFFICE | (931) 232-5968 | |
| COUNTY SHERIFF'S OFFICE | (931) 232-8332 | |
|] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. | | |
| COMMENTS: | | |
| Suggested List of Equipment to conduct the Inspection Latest Bridge Inspection Report | on: | |
| Scour POA Report with the above Checklist | | |
| Bridge Design Plans, if available | | |
| Tape measure with weight | | |
| Plumb bob | | |
| Range Pole | | |
| A 1000 Foot Roll of yellow Polyethylene Barricade Tap | e printed with the following message: | |
| SAFETY HAZARD KEEP A | WAY | |

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19