## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



BRIDGE ID NUMBER: 810A2560001 BRIDGE OWNER: STEWART COUNTY ROAD NAME: ELK CR RD

CROSSING: LITTLE DRY ELK CREEK

LATITUDE:: N 36.38275 DEGREES LONGITUDE: W 87.72717 **DEGREES** 

COUNTY: STEWART ROUTE: 0A283 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 1.32 YEAR BUILT: 1978

		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O		: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON CONCRETE SPREAD FOO	TING FOUNDATION	
BENTS:	NOT APPLICABLE			
PIERS:	CONCRETE SOLID SHAFT PIER ON	CONCRETE SPREAD FOOTING F	OUNDATION	
		SCOUR EVALUATION		
Bridge has I	unknown foundations. Pick of eco		e bridge shall be monitored for distress	
	icant flood events. Monitor bridge			
		INSPECTION PROCEDURES		
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert		
		[ ] TDOT District or Loc	cal Maintenance Personnel	
		[ ] THP or Local Law E	nforcement Personnel	
		[ ] Other:		
Things to c	<u>heck on a bridge during floods</u>	<u>:</u>		
[ ] - Span	movement - horizontally as we	ell as vertically		
1. 0	Check displacement / deflection	n along curb line, both brid	ge rails and outer edge of bridge deck.	
2. 0	Check for plumb of piers or ber	its.		
[ ] - Chec	k for embankment erosion			
[ ] - Chec	k for drift build-up on piers or	bents		
[ ] - Chec	k pier exposure, if possible, an	d compare to previous insp	pection	
[ ] - Review the latest bridge inspection report versus current field conditions				
lf Clasura is	recommended:			
Coun temp	ity or City Maintenance Person	nel. Use Barricade Tape, tra	ecured and properly closed by District, affic cones and/or traffic flares as e until such time as the bridge may	
-	] - Contact: (1) District Maintenance Supervisor ( if bridge is State maintained )			
	• •		oridge is not State maintained )	
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	•	cement Officers as appropriate	
	(4) TDOT Regional Bridge		1 F F	
[ ] - The E	• • • • • • • • • • • • • • • • • • • •	•	daylight visual inspection is made	
	TDOT bridge inspection team.		•	

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[ ] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any bridg prior to signing the detour route.	ge on the selected detour route shall be checked			
[ ] - The bridge can be re-opened only after a TDOT k	e bridge can be re-opened only after a TDOT bridge inspection team checks the substructure nits and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:			
COUNTY MAYOR'S OFFICE	(931) 232-3100			
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 232-5968			
COUNTY SHERIFF'S OFFICE	(931) 232-8332			
The report shall include the date and time of the as appropriate, photographs of the bridge and st scouring has occurred, the report shall also be c	ream channel measurements. If significant opied to Bridge Inspection Headquarters.			
Suggested List of Equipment to conduct the Inspection	<u>n:</u>			
Latest Bridge Inspection Report				
Scour POA Report with the above Checklist				
Bridge Design Plans, if available				
Tape measure with weight				
Plumb bob				
Range Pole				
A 1000 Foot Roll of yellow Polyethylene Barricade Tape	e printed with the following message:			

**SAFETY HAZARD KEEP AWAY** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

**TDOT radio directory (State Personnel only)** 

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape