HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 84014730007
BRIDGE OWNER: TIPTON COUNTY
ROAD NAME: OLD MEMPHIS RD

CROSSING: BRANCH

LATITUDE:: N 35.50311 DEGREES
LONGITUDE: W 89.67742 DEGREES

COUNTY: TIPTON
ROUTE: 01473
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.72
YEAR BUILT: 1991

LON	NGITUDE: W 89.67742 DEGREES	YEAR BUILT: 1991	
MAIN SPAN:	CONCRETE - CHANNEL BEAM	TYPE OF SUPERSTRUCTURE APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FOU		
BENTS:	NOT APPLICABLE	NO THON	
PIERS:	NOT APPLICABLE		
TIENO.	NOT AT TEICABLE		
		SCOUR EVALUATION	
•		our cannot be determined. The bridge shall be monitored for distress e in lieu of installing scour countermeasures.	
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
Things to c	<u>heck on a bridge during flood</u>	<u>s:</u>	
	movement - horizontally as w	-	
	•	n along curb line, both bridge rails and outer edge of bridge deck.	
	Check for plumb of piers or be	nts.	
	k for embankment erosion		
	k for drift build-up on piers or		
[] - Check pier exposure, if possible, and compare to previous inspection			
[] - Revie	ew the latest bridge inspection	report versus current field conditions	
lf Closura is	recommended:		
Coun temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may	
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer Engineer	
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(901) 476-0200		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(901) 837-5900		
COUNTY SHERIFF'S OFFICE	(901) 475-3300		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Inspect	tion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole A 1000 Foot Roll of yellow Polyethylene Barricade Ta	ane printed with the following message:		
SAFETY HAZARD KEEP			

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape