## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 84F00030007
BRIDGE OWNER: TIPTON COUNTY
ROAD NAME: BRIDE RD
CROSSING: MATHIS CREEK

LATITUDE:: N 35.59400 DEGREES
LONGITUDE: W 89.71122 DEGREES

COUNTY: TIPTON
ROUTE: 00808
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 5.07
YEAR BUILT: 1965

	TOTAL STATE OF THE	TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN: NOT APPLICABLE
WAIN SPAN.	CONCRETE - CHANNEL BEAM	AFFR. SFAN. NOT AFFLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FOU	INDATION
BENTS:	TIMBER PILE BENT ON PILE FOUN	DATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
	our critical; bridge foundations de sures are installed but they are n	etermined to be unstable for calculated scour conditions. No scour needed.
		- INSPECTION PROCEDURES -
What Initiat	ted the Call-out Inspection?	[ ] BridgeWatch Alert
What initiated the Gail-out inspection:		[ ] TDOT District or Local Maintenance Personnel
		[ ] THP or Local Law Enforcement Personnel
		[ ] Other:
		[ ] • • • • • • • • • • • • • • • • • •
Things to c	heck on a bridge during floods	<u>s:</u>
_	movement - horizontally as w	
		on along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	
	k for embankment erosion	
	k for drift build-up on piers or	hents
	• •	nd compare to previous inspection
		report versus current field conditions
[ ] - KCVK	w the latest bridge inspection	report versus current field conditions
If Closure is	recommended:	
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	Supervisor ( if bridge is State maintained )
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed u TDOT bridge inspection team.	intil the water recedes and a daylight visual inspection is made

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



off	•	e District maintenance or local highway maintenance dge on the selected detour route shall be checked	
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CO	NTACT PERSONNEL:	TELEPHONE NUMBER:	
CO	UNTY MAYOR'S OFFICE	(901) 476-0200	
HW	Y. CHIEF ADMINISTRATOR'S OFFICE	(901) 837-5900	
CO	UNTY SHERIFF'S OFFICE	(901) 475-3300	
The as a	report shall include the date and time of the	ction to BridgeWatch scour monitoring system. e inspection, a brief summary of findings and, stream channel measurements. If significant copied to Bridge Inspection Headquarters.	
COMMENT	TS:		
Suggeste	ed List of Equipment to conduct the Inspection	on:	
Latest Br	idge Inspection Report		
Scour PC	A Report with the above Checklist		
Bridge De	esign Plans, if available		
•	asure with weight		
Plumb bo			
Range Po			
A 1000 F	oot Roll of yellow Polyethylene Barricade Ta		
	SAFETY HAZARD KEEP	AWAY	

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape