HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 84S80710015
BRIDGE OWNER: TIPTON COUNTY
ROAD NAME: GAINESVILLE RD

CROSSING: BRANCH

LATITUDE:: N 35.41244 DEGREES LONGITUDE: W 89.57242 DEGREES

COUNTY: TIPTON
ROUTE: 00810
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 8.15

| LON | IGITUDE: W 89.57242 DEGREES | YEAR BUILT: 1954 | |
|---|--|--|--|
| | | TYPE OF SUPERSTRUCTURE | |
| MAIN SPAN: | CONCRETE - CHANNEL BEAM | APPR. SPAN: NOT APPLICABLE | |
| | | TYPE OF SUBSTRUCTURE | |
| ABUTMENTS: | CONCRETE STUB ABUTMENT ON C | ONCRETE PILE FOUNDATION | |
| BENTS: | CONCRETE PILE BENT ON PILE FO | UNDATION | |
| PIERS: | NOT APPLICABLE | | |
| | | SCOUR EVALUATION | |
| - | our critical; bridge foundations de ing scour countermeasures. | termined to be unstable for calculated scour conditions. Monitor bridge in | |
| | | INSPECTION PROCEDURES | |
| What Initiated the Call-out Inspection? | | [] BridgeWatch Alert | |
| | | [] TDOT District or Local Maintenance Personnel | |
| | | [] THP or Local Law Enforcement Personnel | |
| | | [] Other: | |
| | | | |
| Things to c | heck on a bridge during floods | <u>:</u> | |
| [] - Span | movement - horizontally as we | ell as vertically | |
| 1. C | Check displacement / deflection | n along curb line, both bridge rails and outer edge of bridge deck. | |
| | Check for plumb of piers or ber | its. | |
| | k for embankment erosion | | |
| | k for drift build-up on piers or | | |
| | | d compare to previous inspection | |
| [] - Revie | w the latest bridge inspection | report versus current field conditions | |
| | | | |
| If Closure is | recommended: | | |
| | | cross road until bridge is secured and properly closed by District, | |
| | | nel. Use Barricade Tape, traffic cones and/or traffic flares as | |
| | | ists to stay off of the bridge until such time as the bridge may | |
| - | operly closed and barricaded. | | |
| [] - Conta | | upervisor (if bridge is State maintained) | |
| | (2) City or County Highway | y Maintenance Official (if bridge is not State maintained) | |
| | (3) Tennessee Highway Pa | trol and/or local law enforcement Officers as appropriate | |
| | (4) TDOT Regional Bridge | Engineer | |
| | The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. | | |

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



| | th State District maintenance or local highway maintenance Any bridge on the selected detour route shall be checked | | |
|---|---|--|--|
| | The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. | | |
| CONTACT PERSONNEL: | TELEPHONE NUMBER: | | |
| COUNTY MAYOR'S OFFICE | (901) 476-0200 | | |
| HWY. CHIEF ADMINISTRATOR'S OFFICE | (901) 837-5900 | | |
| COUNTY SHERIFF'S OFFICE | (901) 475-3300 | | |
| - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. | | | |
| COMMENTS: | | | |
| Suggested List of Equipment to conduct the li | nspection: | | |
| Latest Bridge Inspection Report | | | |
| Scour POA Report with the above Checklist | | | |
| Bridge Design Plans, if available | | | |
| Tape measure with weight | | | |
| Plumb bob | | | |
| Range Pole | | | |
| A 1000 Foot Roll of yellow Polyethylene Barrio | | | |
| SAFETY HAZARD | KEEP AWAY | | |

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24