HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 84SR0010001 COUNTY: TIPTON
BRIDGE OWNER: STATE OF TENNESSEE ROUTE: SR001
ROAD NAME: HWY 70 W SPECIAL CASE: 0
CROSSING: E. FORK BEAVER CK CANAL
LATITUDE:: N 35.40453 DEGREES LOG MILE: 0.07

LON	NGITUDE: W 89.545/5 DEGREES		YEAR BUILT: 1923
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE - BOX GIRDERS - MULTIPLE	BEAM OR APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	ENT ON CONCRETE SPREAD FOOTI	NG FOUNDATION
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
	our critical; bridge foundations de stalled but is in poor condition. S		culated scour conditions. Rip-rap protection on system are needed.
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection		[] BridgeWatch Alert	
	·	[] TDOT District or Loca	al Maintenance Personnel
		[] THP or Local Law En	forcement Personnel
		[] Other:	
[] - Span 1. 0 2. 0 [] - Chec [] - Chec [] - Revie	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, and the latest bridge inspection	ell as vertically n along curb line, both bridg nts. bents nd compare to previous insp	
<u>If Closure is</u>	recommended:		
Coun temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State	maintained)
	(2) City or County Highwa	y Maintenance Official (if b	ridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any bridg prior to signing the detour route.	ge on the selected detour route shall be checked		
[] - The bridge can be re-opened only after a TDOT b units and they are determined to be structurally s	ge can be re-opened only after a TDOT bridge inspection team checks the substructure		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
The report shall include the date and time of the i as appropriate, photographs of the bridge and str scouring has occurred, the report shall also be co	ream channel measurements. If significant opied to Bridge Inspection Headquarters.		
Suggested List of Equipment to conduct the Inspection	<u>ı:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape			
SAFETY HAZARD KEEP AV	NAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24