HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 84SR0540009

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: HWY 54

CROSSING: BRIGMON BRANCH

LATITUDE:: N 35.56100 DEGREES
LONGITUDE: W 89.51078 DEGREES

COUNTY: TIPTON
ROUTE: SR054
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 8.12

LON	IGITUDE: W 89.51078 DEGREES	3	YEAR BUILT: 1956
MAIN SPAN:	CONCRETE - TEE BEAM	 TYPE OF SUPERSTRUCTURE = APPR. SPAN: 	NOT APPLICABLE
		TYPE OF CUPCTRUCTURE	
ARI ITMENTS:	CONCRETE STUB ABUTMENT ON (TYPE OF SUBSTRUCTURE =	
BENTS:	CONCRETE PILE BENT ON PILE FO		
PIERS:	NOT APPLICABLE	JONDATION	
FILING.	NOT APPLICABLE		
		SCOUR EVALUATION	
	our critical; bridge foundations de stalled and is in fair condition. So		culated scour conditions. Rip-rap protection tion system are needed.
		- INSPECTION PROCEDURES -	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
	·		al Maintenance Personnel
		[] THP or Local Law En	forcement Personnel
Things to cl	heck on a bridge during floods	<u>s:</u>	
1. C	•	n along curb line, both bridge	e rails and outer edge of bridge deck.
	Check for plumb of piers or be	nts.	
	k for embankment erosion k for drift build-up on piers or	honts	
	• •		action
	k pier exposure, if possible, a w the latest bridge inspection		
[] - Kevie	w the latest bridge inspection	report versus current neid c	onditions
If Closure is	recommended:		
[] - Stay a Coun temp	at bridge with vehicle pulled a ty or City Maintenance Persor	nnel. Use Barricade Tape, trat rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State	maintained)
	(2) City or County Highwa	y Maintenance Official (if br	ridge is not State maintained)
			ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	-
	The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ate District maintenance or local highway maintenance oridge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report	ction:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:		
SAFETY HAZARD KEE	P AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24