## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 86I00260031

BRIDGE OWNER: **STATE OF TENNESSEE**ROAD NAME: **JAMES H QUILLEN PKWY** 

CROSSING: INDIAN CREEK

LATITUDE:: N 36.14167 DEGREES
LONGITUDE: W 82.43000 DEGREES

COUNTY: UNICOI
ROUTE: 10026
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 10.31
YEAR BUILT: 1977

LON	NGHODE: W 82.43000 DEGREES	YEAR BUILT: 1977
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	PRESTRESSED CONCRETE - STRIN OR GIRDER	GER/MULTI-BEAM APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON ROCK FOUNDATION
BENTS:	NOT APPLICABLE	
PIERS:	CONCRETE SOLID SHAFT PIER ON	CONCRETE SPREAD FOOTING FOUNDATION
		SCOUR EVALUATION
	our critical; bridge foundations de ling scour countermeasures.	termined to be unstable for calculated scour conditions. Monitor bridge in
		INSPECTION PROCEDURES
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert
		[ ] TDOT District or Local Maintenance Personnel
		[ ] THP or Local Law Enforcement Personnel
		[ ] Other:
1. C 2. C [ ] - Chec [ ] - Chec [ ] - Chec	Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, an	n along curb line, both bridge rails and outer edge of bridge deck. ats.
If Closure is	recommended:	
Coun temp	nty or City Maintenance Person	cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State maintained )
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )
	(3) Tennessee Highway Pa	trol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.	

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	Il work with State District maintenance or local highway maintenance ur route. Any bridge on the selected detour route shall be checked te.		
	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(865) 712-8292		
DISTRICT MAINTENANCE SUPERVISO	OR (423) 202-5393		
TENNESSEE HIGHWAY PATROL	(423) 348-6144		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to cond	duct the Inspection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Ch	necklist		
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethyle	ene Barricade Tape printed with the following message:		
SAFETY	HAZARD KEEP AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24