HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 88SR0300007

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: SR30

CROSSING: CANE CREEK

COUNTY: VAN BUREN ROUTE: SR030 SPECIAL CASE: 0 COUNTY SEQUENCE: 1

LOC MILE. 4440

	CITUDE: N 35.74338 DEGREE		
LON	GITUDE: W 85.39360 DEGREE	YEAR BUILT: 1982	
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE CONT BEAM OR GIRDERS - SINGLE OR		
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON SOIL FOUNDATION		
BENTS:	S: NOT APPLICABLE		
PIERS:	CONCRETE HAMMERHEAD PIER	ON STEEL PILE FOUNDATION	
		SCOUR EVALUATION	
	our critical; bridge foundations ding scour countermeasures.	etermined to be unstable for calculated scour conditions. Monitor bridge in	
		- INSPECTION PROCEDURES -	
What Initiate	ed the Call-out Inspection?	[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
[] - Span 1. C 2. C [] - Checl [] - Checl	check for plumb of piers or be k for embankment erosion k for drift build-up on piers of k pier exposure, if possible, a	vell as vertically on along curb line, both bridge rails and outer edge of bridge deck. onts.	
f Closure is	recommended:		
Coun temp	ty or City Maintenance Perso	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may.	
[] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)			
	(2) City or County Highw	ay Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway F	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridg	e Engineer	
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



	icials in establishing a detour route. Any bric or to signing the detour route.	lge on the selected detour route shall be checked	
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CO	NTACT PERSONNEL:	TELEPHONE NUMBER:	
REG	GION BRIDGE ENGINEER	(423) 290-7467	
DIS	TRICT MAINTENANCE SUPERVISOR	(931) 434-1713	
TEN	NNESSEE HIGHWAY PATROL	(931) 528-8496	
as a sco	e report shall include the date and time of the appropriate, photographs of the bridge and souring has occurred, the report shall also be	copied to Bridge Inspection Headquarters.	
Suggeste	ed List of Equipment to conduct the Inspection	on:	
	idge Inspection Report		
	A Report with the above Checklist		
_	esign Plans, if available		
-	asure with weight		
Plumb bo			
Range Po			
A 1000 F	oot Roll of yellow Polyethylene Barricade Tap		
	SAFETY HAZARD KEEP A	AWAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24