HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 88SR1110008

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: SR111

CROSSING: CANEY FORK RIVER

COUNTY: VAN BUREN ROUTE: SR111 SPECIAL CASE: 0 COUNTY SEQUENCE: 1

	.TITUDE:: N 35.82137 DEGREE IGITUDE: W 85.46153 DEGREE		
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	STEEL CONTINUOUS - STRINGER GIRDER	MULTI-BEAM OR APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	STEEL PILE FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE HAMMERHEAD PIER	ON STEEL PILE FOUNDATION	
		SCOUR EVALUATION	
	ioration of channel protection or	s have been installed to reduce the risk of bridge failure during a flood riprap should be reported to TDOT for assessment. Substructure units are	
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection		[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
[] - Span 1. C 2. C [] - Chec [] - Chec	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers of k pier exposure, if possible, a	vell as vertically on along curb line, both bridge rails and outer edge of bridge deck. ents.	
lf Closure is	recommended:		
Coun temp	ity or City Maintenance Perso	across road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as brists to stay off of the bridge until such time as the bridge may.	
[] - Conta	ct: (1) District Maintenance Supervisor (if bridge is State maintained)		
	(2) City or County Highw	ay Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway F	Patrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridg	e Engineer	
	Bridge should remain closed of TDOT bridge inspection team	until the water recedes and a daylight visual inspection is made .	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



officials in establishing a detour route. Any brid prior to signing the detour route.	ge on the selected detour route shall be checked		
The bridge can be re-opened only after a TDOT	bridge can be re-opened only after a TDOT bridge inspection team checks the substructure s and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(423) 290-7467		
DISTRICT MAINTENANCE SUPERVISOR	(931) 434-1713		
TENNESSEE HIGHWAY PATROL	(931) 528-8496		
scouring has occurred, the report shall also be o			
Suggested List of Equipment to conduct the Inspection	<u>on:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap	pe printed with the following message:		
SAFETY HAZARD KEEP A	WAY		
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			
Traffic Cones - Minimum of four (4)			
Traffic Safety Flares - Minimum of four (4) or set of ele	ectronic warning flashers		

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)