HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: WARREN

BRIDGE ID NUMBER: 89003880001
BRIDGE OWNER: WARREN COUNTY
ROAD NAME: SHELBYVILLE RD

CROSSING: N.PRONG BARREN FORK RIVE
LATITUDE:: N 35.66668 DEGREES
LONGITUDE: W 85.96585 DEGREES

ROUTE: 01114

SPECIAL CASE: 0

COUNTY SEQUENCE: 1

LOG MILE: 1.69

LON	IGITUDE: W 85.96585 DEGREES		YEAR BUILT: 1977	
		TYPE OF SUPERSTRUCTURE =		
MAIN SPAN:	PRESTRESSED CONCRETE CONTIL STRINGER/MULTI-BEAM OR GIRDE		NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE -		
ABUTMENTS:	TMENTS: CONCRETE STUB ABUTMENT ON STEEL PILE FOUNDATION TS: NOT APPLICABLE			
BENTS:				
PIERS:	CONCRETE HAMMERHEAD PIER O	N UNKNOWN FOUNDATION		
		SCOUR EVALUATION =		
	inknown foundations. Risk of sco icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.	
		INSPECTION PROCEDURES =		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		[] TDOT District or Loca	al Maintenance Personnel	
		[] THP or Local Law En	forcement Personnel	
		[] Other:		
[] - Span 1. C 2. C [] - Chec [] - Chec	heck on a bridge during floods movement - horizontally as we check displacement / deflection check for plumb of piers or bein k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, ar we the latest bridge inspection	ell as vertically n along curb line, both bridg nts. bents nd compare to previous inspe		
f Closure is	recommended:			
Coun temp	ty or City Maintenance Persor	nel. Use Barricade Tape, traf	cured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may	
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State	maintained)	
	(2) City or County Highwa	y Maintenance Official (if br	idge is not State maintained)	
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	idge should remain closed until the water recedes and a daylight visual inspection is made			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



	icials in establishing a detour route. Any bric or to signing the detour route.	lge on the selected detour route shall be checked		
	e bridge can be re-opened only after a TDOT its and they are determined to be structurally	n be re-opened only after a TDOT bridge inspection team checks the substructure		
COI	NTACT PERSONNEL:	TELEPHONE NUMBER:		
COL	UNTY MAYOR'S OFFICE	(931) 473-2505		
HW	Y. CHIEF ADMINISTRATOR'S OFFICE	(931) 473-2007		
COI	UNTY SHERIFF'S OFFICE	(931) 473-7863		
The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. COMMENTS:				
Suggeste	ed List of Equipment to conduct the Inspection	on:		
Latest Br	idge Inspection Report			
Scour PO	A Report with the above Checklist			
_	esign Plans, if available			
-	asure with weight			
Plumb bo				
Range Po				
A 1000 Fo	oot Roll of yellow Polyethylene Barricade Tap			
	SAFETY HAZARD KEEP A	AWAY		

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)