HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 89021380003 BRIDGE OWNER: WARREN COUNTY ROAD NAME: HILLS CREEK RD. CROSSING: HILLS CREEK

LATITUDE:: N 35.56884 DEGREES

COUNTY: WARREN ROUTE: 02138 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 2.97

LON	IGITUDE: W 85.67974 DEGREES		YEAR BUILT: 1961	
		TYPE OF SUPERSTRUCTURE -		
MAIN SPAN:	PRESTRESSED CONCRETE - BOX E GIRDERS - MULTIPLE	BEAM OR APPR. SPAN:	NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE -		
ABUTMENTS:	CONCRETE STUB ABUTMENT ON S	TEEL PILE FOUNDATION		
BENTS:	CONCRETE COLUMN TWO POST B	ENT ON ROCK FOUNDATION		
PIERS:	CONCRETE COLUMNS WITH SOLID	WEB WALL (DUMB BELL) ON STEE	L PILE FOUNDATION	
		SCOUR EVALUATION —		
	our critical; bridge foundations de ing scour countermeasures.	termined to be unstable for calc	culated scour conditions. Monitor bridge in	
		INSPECTION PROCEDURES -		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
	•	[] TDOT District or Local	Maintenance Personnel	
		[] THP or Local Law Enfo	orcement Personnel	
		[] Other:		
1. C 2. C [] - Chec [] - Chec	movement - horizontally as we check displacement / deflection check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, an ew the latest bridge inspection	n along curb line, both bridge nts. bents Id compare to previous inspe		
If Closure is	recommended:			
Coun temp	ity or City Maintenance Person	nel. Use Barricade Tape, traff	ured and properly closed by District, ic cones and/or traffic flares as intil such time as the bridge may	
[] - Conta				
	(2) City or County Highwa	y Maintenance Official (if bri	dge is not State maintained)	
	(3) Tennessee Highway Pa	atrol and/or local law enforcer	nent Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	th State District maintenance or local highway maintenance Any bridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 473-2505		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 473-2007		
COUNTY SHERIFF'S OFFICE	(931) 473-7863		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the li	nspection:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barric	ade Tape printed with the following message:		
SAFFTY HAZARD			

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24