## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 89021870003
BRIDGE OWNER: WARREN COUNTY
ROAD NAME: LUCKY RD.

CROSSING: MOUNTAIN CREEK
LATITUDE:: N 35.81428 DEGREE

LATITUDE:: N 35.81428 DEGREES LONGITUDE: W 85.85750 DEGREES

COUNTY: WARREN
ROUTE: 02187
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 5.51
YEAR BUILT: 1955

2011	1011002. II 00.00700 D2011220		TEAR BOILT. 1000
		TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON C	CONCRETE PILE FOUNDATION	
BENTS:	CONCRETE PILE BENT ON PILE FO	UNDATION	
PIERS:	CONCRETE COLUMNS WITH SOLID	WEB WALL (DUMB BELL) ON TIMI	BER PILE FOUNDATION
		SCOUR EVALUATION =	
Dridge is see	our ouition. It wides formed ations de		levileted engine conditions. Die von protection
•	stalled but is in poor condition. Si		lculated scour conditions. Rip-rap protection on system are needed.
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection		[ ] BridgeWatch Alert	
	·	•	al Maintenance Personnel
		[ ] THP or Local Law Ent	forcement Personnel
		[ ] Other:	
Things to c	heck on a bridge during floods	<u>s:</u>	
[ ] - Span	movement - horizontally as w	ell as vertically	
	_		e rails and outer edge of bridge deck.
	Check for plumb of piers or be		
	k for embankment erosion		
	k for drift build-up on piers or	bents	
	k pier exposure, if possible, ar		ection
	ew the latest bridge inspection		
<u>lf Closure is</u>	recommended:		
Coun temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, trat rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State	maintained )
	(2) City or County Highwa	y Maintenance Official (if br	ridge is not State maintained )
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	tate District maintenance or local highway maintenance bridge on the selected detour route shall be checked		
	- The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 473-2505		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 473-2007		
COUNTY SHERIFF'S OFFICE	(931) 473-7863		
The report shall include the date and time of as appropriate, photographs of the bridge ar	<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.</li> <li>The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.</li> </ul>		
COMMENTS:			
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report	ection:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:		
SAFETY HAZARD KE			

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24