HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 890A0540001

BRIDGE OWNER: WARREN COUNTY

ROAD NAME: SNEED RD

CROSSING: SMALL BRANCH

LATITUDE:: N 35.82369 DEGREES LONGITUDE: W 85.88440 DEGREES

COUNTY: WARREN
ROUTE: 0A054
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.21

| LON | NGITUDE: W 85.88440 DEGREES | | YEAR BUILT: 1960 |
|--|---|---|--|
| | | TYPE OF SUPERSTRUCTURE - | |
| MAIN SPAN: | CONCRETE - CULVERT (INCLUDES CULVERTS) | FRAME APPR. SPAN: | NOT APPLICABLE |
| | | TYPE OF SUBSTRUCTURE - | |
| ABUTMENTS: | CONCRETE BOX TYPE ON CONCRI | ETE SPREAD FOOTING FOUNDATIO | N |
| BENTS: | NOT APPLICABLE | | |
| PIERS: | NOT APPLICABLE | | |
| | | SCOUR EVALUATION = | |
| | unknown foundations. Risk of sco icant flood events. Monitor bridge | | bridge shall be monitored for distress termeasures. |
| | | INSPECTION PROCEDURES - | |
| What Initiated the Call-out Inspection? | | [] BridgeWatch Alert | |
| | · | [] TDOT District or Loca | ıl Maintenance Personnel |
| | | [] THP or Local Law Enf | orcement Personnel |
| | | [] Other: | |
| 1. C 2. C [] - Chec [] - Chec | movement - horizontally as w Check displacement / deflectio Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, ar ew the latest bridge inspection | n along curb line, both bridgents. bents nd compare to previous inspe | |
| If Closure is | recommended: | | |
| Coun temp | nty or City Maintenance Persor | nnel. Use Barricade Tape, traf | ured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may |
| [] - Conta | act: (1) District Maintenance S | Supervisor (if bridge is State | maintained) |
| | (2) City or County Highwa | y Maintenance Official (if br | idge is not State maintained) |
| | (3) Tennessee Highway Pa | atrol and/or local law enforce | ment Officers as appropriate |
| | (4) TDOT Regional Bridge | Engineer | |
| | The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. | | |

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



| | state District maintenance or local highway maintenance bridge on the selected detour route shall be checked | | |
|---|---|--|--|
| [] - The bridge can be re-opened only after a TD units and they are determined to be structure. | The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. | | |
| CONTACT PERSONNEL: | TELEPHONE NUMBER: | | |
| COUNTY MAYOR'S OFFICE | (931) 473-2505 | | |
| HWY. CHIEF ADMINISTRATOR'S OFFICE | (931) 473-2007 | | |
| COUNTY SHERIFF'S OFFICE | (931) 473-7863 | | |
| Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. | | | |
| COMMENTS: | | | |
| Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report Scour POA Report with the above Checklist Bridge Design Plans, if available | ection: | | |
| Tape measure with weight | | | |
| Plumb bob | | | |
| Range Pole | | | |
| A 1000 Foot Roll of yellow Polyethylene Barricade | Tape printed with the following message: | | |
| SAFETY HAZARD KEI | ΕΡ ΛΜΑΥ | | |

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape