HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 890A4370001
BRIDGE OWNER: WARREN COUNTY
ROAD NAME: CHESTNUT GROVE RD

CROSSING: FULTZ CREEK

LATITUDE:: N 35.51710 DEGREES LONGITUDE: W 85.82047 DEGREES

COUNTY: WARREN
ROUTE: 0A437
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.53
YEAR BUILT: 1963

201	1011002. 11 00.02047 D2011220			12/11(BOIL 1. 1000
		TYPE OF SUPERSTRUCTU	RE =	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	R GIRDER APPR. S	SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTUR	E -	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON UNKNOWN FOUNDAT	ION	
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
Bridge has I	unknown foundations. Disk of sor		Tho	bridge shall be monitored for distress
	ficant flood events. Monitor bridge			
		INSPECTION PROCEDURE	ES -	
What Initiated the Call-out Inspection?		[] BridgeWatch Ale	ert	
	·	-		al Maintenance Personnel
				forcement Personnel
Things to c	heck on a bridge during floods	<u>s:</u>		
[] - Span	n movement - horizontally as w	ell as vertically		
	-		bridae	e rails and outer edge of bridge deck.
	Check for plumb of piers or bei	=	J	3 3
	k for embankment erosion			
	k for drift build-up on piers or	bents		
	ck pier exposure, if possible, ar		inspe	ection
	ew the latest bridge inspection	•	-	
<u>lf Closure is</u>	s recommended:			
Cour temp	nty or City Maintenance Person	nel. Use Barricade Tap	e, traf	eured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is	State	maintained)
	(2) City or County Highwa	y Maintenance Official	(if br	idge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law er	force	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer		-
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route. 	District maintenance or local highway maintenance ge on the selected detour route shall be checked				
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.				
CONTACT PERSONNEL:	TELEPHONE NUMBER:				
COUNTY MAYOR'S OFFICE	(931) 473-2505				
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 473-2007				
COUNTY SHERIFF'S OFFICE	(931) 473-7863				
[] - Summarize and submit findings from the inspect The report shall include the date and time of the as appropriate, photographs of the bridge and street scouring has occurred, the report shall also be considered.	inspection, a brief summary of findings and, tream channel measurements. If significant				
COMMENTS:					
Suggested List of Equipment to conduct the Inspection	<u>n:</u>				
Latest Bridge Inspection Report					
Scour POA Report with the above Checklist					
Bridge Design Plans, if available					
Tape measure with weight					
Plumb bob					
Range Pole					
A 1000 Foot Roll of yellow Polyethylene Barricade Tap					
SAFETY HAZARD KEEP A	WAY				

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24