HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 89\$42570009

BRIDGE OWNER: STATE OF TENNESSEE
ROAD NAME: GREEN HILL RD
CROSSING: MOUNTAIN CREEK

LATITUDE:: N 35.81788 DEGREES LONGITUDE: W 85.87763 DEGREES

COUNTY: WARREN
ROUTE: SR287
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 21.81

LON	NGITUDE: W 85.87763 DEGREES		YEAR BUILT: 1977
		TYPE OF SUPERSTRUCTURE =	
MAIN SPAN:	PRESTRESSED CONCRETE CONTIN STRINGER/MULTI-BEAM OR GIRDE		NOT APPLICABLE
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON U	INKNOWN FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE HAMMERHEAD PIER OF	N UNKNOWN FOUNDATION	
		SCOUR EVALUATION =	
	unknown foundations. Risk of sco icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.
		INSPECTION PROCEDURES -	
What Initiated the Call-out Inspection		[] BridgeWatch Alert	
		[] TDOT District or Loca	al Maintenance Personnel
		[] THP or Local Law Ent	forcement Personnel
		[] Other:	
[] - Span 1. C 2. C [] - Chec [] - Chec	heck on a bridge during floods movement - horizontally as we check displacement / deflection check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, ar ew the latest bridge inspection	ell as vertically n along curb line, both bridge nts. bents nd compare to previous inspe	
<u>If Closure is</u>	recommended:		
Coun temp	ity or City Maintenance Person	nel. Use Barricade Tape, traf	cured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State	maintained)
	(2) City or County Highwa	y Maintenance Official (if br	idge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ate District maintenance or local highway maintenance oridge on the selected detour route shall be checked		
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(423) 290-7467		
DISTRICT MAINTENANCE SUPERVISOR	(931) 434-1713		
TENNESSEE HIGHWAY PATROL	(931) 528-8496		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report	ction:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade			
SAFETY HAZARD KEE	P AWAY		

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)