## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 91017650001
BRIDGE OWNER: WAYNE COUNTY

ROAD NAME: RAILROAD BED-IRON CITY RD

CROSSING: HOLLY CREEK

LATITUDE:: N 35.03600 DEGREES
LONGITUDE: W 87.58553 DEGREES

COUNTY: WAYNE
ROUTE: 01765
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.08
YEAR BUILT: 1960

20.	1011052. II 01.50000 BEGINEE	T/DE 05 011D5D0TD110T11D5	12/11/201211 1000
MAIN ODAN	201100575 755 0544	TYPE OF SUPERSTRUCTURE =	NOT APPLICABLE
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON CONCRETE SPREAD FOOTI	NG FOUNDATION
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE HAMMERHEAD PIER OF	N ROCK FOUNDATION	
		SCOUR EVALUATION =	
Bridge has u	unknown foundations. Risk of sco	our cannot be determined. The	bridge shall be monitored for distress
	icant flood events. Monitor bridge		
		INSPECTION PROCEDURES =	
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert	
		•	al Maintenance Personnel
		[ ] THP or Local Law En	
		[ ] Other:	
Things to c	<u>heck on a bridge during floods</u>	<u>s:</u>	
[ ] - Span	movement - horizontally as we	ell as vertically	
1. 0	Check displacement / deflection	n along curb line, both bridg	e rails and outer edge of bridge deck.
2. 0	Check for plumb of piers or ber	nts.	
[ ] - Chec	k for embankment erosion		
[ ] - Chec	k for drift build-up on piers or	bents	
[ ] - Chec	k pier exposure, if possible, ar	nd compare to previous inspe	ection
[ ] - Revie	ew the latest bridge inspection	report versus current field c	onditions
lf Clasura ia	, recommended.		
	recommended:		
Coun temp	nty or City Maintenance Person	nel. Use Barricade Tape, tra	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State	maintained )
	(2) City or County Highwa	y Maintenance Official ( if br	ridge is not State maintained )
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[ ] - The bridge inspection team will work with State District maintenance or local highway maintenance



	officials in establishing a detour route. Any b prior to signing the detour route.	ridge on the selected detour route shall be checked		
		dge can be re-opened only after a TDOT bridge inspection team checks the substructure nd they are determined to be structurally stable.		
	CONTACT PERSONNEL:	TELEPHONE NUMBER:		
	COUNTY MAYOR'S OFFICE	(931) 722-3653		
	HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 722-5556		
	COUNTY SHERIFF'S OFFICE	(931) 722-3613		
<b>.</b>				
Sugge	sted List of Equipment to conduct the Inspec	etion:		
Latest	Bridge Inspection Report			
Scour	POA Report with the above Checklist			
Bridge	Design Plans, if available			
Tape r	neasure with weight			
Plumb	bob			
Range				
A 1000	Foot Roll of yellow Polyethylene Barricade 1			
	SAFETY HAZARD KEEI	P AWAY		

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape