HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 910A2830001
BRIDGE OWNER: WAYNE COUNTY

ROAD NAME: FIRSH BUTLER CREEK RD
CROSSING: FIRST BUTLER CREEK
LATITUDE:: N 35.11585 DEGREES
LONGITUDE: W 87.75798 DEGREES

COUNTY: WAYNE
ROUTE: 0A283
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.73

LON	NGITUDE: W 87.75798 DEGREE	S	YEAR BUILT: 1984
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	CONCRETE CONTINUOUS - CULV FRAME CULVERTS)	ERT (INCLUDES APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE BOX TYPE ON CONCR	RETE SPREAD FOOTING FOUNDATI	ON
BENTS:	NOT APPLICABLE		
PIERS:	PIER WALL FOR CONCRETE BOX	ON CONCRETE SPREAD FOOTING	FOUNDATION
		SCOUR EVALUATION	
event. Deter		r riprap should be reported to T	the risk of bridge failure during a flood DOT for assessment. A permanent scour
		 INSPECTION PROCEDURES 	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
		[] TDOT District or Loc	cal Maintenance Personnel
		• •	nforcement Personnel
		[] Other:	
		_	
Things to c	heck on a bridge during flood	<u>ls:</u>	
	movement - horizontally as v	-	
	•		ge rails and outer edge of bridge deck.
	Check for plumb of piers or be	ents.	
	k for embankment erosion	, banta	
	k for drift build-up on piers o		poetion
	k pier exposure, if possible, a ew the latest bridge inspectio	• • •	
[] - Kevie	ew the latest bridge inspectio	ir report versus current neid	Conditions
lf Clasura is	recommended:		
Coun temp	nty or City Maintenance Perso	onnel. Use Barricade Tape, tra orists to stay off of the bridge	ecured and properly closed by District, affic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance	, , ,	•
	(2) City or County Highw	ay Maintenance Official (if b	oridge is not State maintained)
	` '		ement Officers as appropriate
	(4) TDOT Regional Bridg		
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 722-3653		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 722-5556		
COUNTY SHERIFF'S OFFICE	(931) 722-3613		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Inspec	tion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade T			
SAFETY HAZARD KEEF	PAWAY		
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			

PUBLICATION DATE

Traffic Cones - Minimum of four (4)

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone