HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 92008590009
BRIDGE OWNER: WEAKLEY COUNTY

ROAD NAME: **OLD SR22** CROSSING: **OVERFLOW**

LATITUDE:: N 36.24831 DEGREES
LONGITUDE: W 88.65206 DEGREES

COUNTY: WEAKLEY
ROUTE: 00859
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 10.15
YEAR BUILT: 1950

	101105E: 11 00.00200 PEGNEES	TYPE OF CUREPCTRUCTURE _	12/11/201211 1333
MAIN SPAN:	CONCRETE - TEE BEAM	 TYPE OF SUPERSTRUCTURE = APPR. SPAN: 	NOT APPLICABLE
WAIN SPAN.	CONCRETE - TEE BEAM	APPR. SPAN.	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON CONCRETE SPREAD FOOTI	NG FOUNDATION
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION -	
Bridge has u	inknown foundations. Risk of sco	our cannot be determined. The	bridge shall be monitored for distress
	icant flood events. Monitor bridge		
		INSPECTION PROCEDURES =	
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert	
		•	al Maintenance Personnel
		[] THP or Local Law En	
Things to c	heck on a bridge during floods	<u>s:</u>	
[] - Snan	movement - horizontally as w	ell as vertically	
		•	e rails and outer edge of bridge deck.
	Check for plumb of piers or be	=	o rano anta caso. cago er arrago acom
	k for embankment erosion		
	k for drift build-up on piers or	bents	
	k pier exposure, if possible, ar		ection
	ew the latest bridge inspection		
<u>lf Closure is</u>	recommended:		
Coun temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, traf	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	supervisor (if bridge is State	maintained)
	(2) City or County Highwa	y Maintenance Official (if br	ridge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed u TDOT bridge inspection team.	ntil the water recedes and a	daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	State District maintenance or local highway maintenance y bridge on the selected detour route shall be checked	
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR'S OFFICE	(731) 364-5413	
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 364-2284	
COUNTY SHERIFF'S OFFICE	(731) 364-5454	
- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:		
Suggested List of Equipment to conduct the Insp Latest Bridge Inspection Report	pection:	
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricado	e Tape printed with the following message:	
SAFFTY HAZARD KE	EP AWAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24